

# New Features

## Roller Lacer® Gold Class™



The devis bracket and UHMW polyethylene guide rollers provide additional stability to the lacer head and allow it to transverse with ease across the width of the lacer.



Belt support shelf gently guides belt into open hook points.



Improved, built-in Face Strip storage.



**Flexible Steel Lacing Company**  
2525 Wisconsin Avenue  
Downers Grove, IL 60515-4200 U.S.A.  
Telephone: (630)-971-0150  
Fax: (630)-971-1180  
E-mail: info@flexco.com



- **Lacer head can be driven by a cordless drill** (18 volt or higher); reducing time and fatigue with installing splices. Built-in safety features prevent the lacer head from contacting end plates. A manual drive handle is supplied for use if drill has lost its charge.

- **Improved belt clamping design** provides greater holding force for the belt with the same simple operating procedure.

- **New Face Strip design** eliminates the need for locking levers and back up bars. This not only reduced installation steps and time, but also eliminated common repair parts with previous models.

- **12" (300 mm) additional length** to the tool allows the lacer to be secured easier on conveyor structure, such as side wall pans, for greater stability when lacing.



Drill not included with lacer purchase.

Face Strips sold separately.

### Ordering Information—Roller Lacer®

Belt Width		Roller Lacer® Gold Class™		Roller Lacer® Manual	
in	mm	Ordering Number	Item Code	Ordering Number	Item Code
24"	600	RL-G24	03985	RL-24	03370
36"	900	RL-G36	03986	RL-36	03371
48"	1200	RL-G48	03987	RL-48	03372
60"	1500	RL-G60	03988	RL-60	03375

### Ordering Information—Face Strips

Belt Width		Roller Lacer® Gold Class™		Roller Lacer® Manual	
in	mm	Ordering Number	Item Code	Ordering Number	Item Code
HOOK SIZE; 36, UCM36					
24"	600	FSGOLD36-24	04038	FSMAN36-24	04020
36"	900	FSGOLD36-36	04039	FSMAN36-36	04021
48"	1200	FSGOLD36-48	04040	FSMAN36-48	04022
60"	1500	FSGOLD36-60	04041	FSMAN36-60	04023
HOOK SIZE; 1, UX-1					
24"	600	FSGOLD1-24	04034	FSMAN1-24	04015
36"	900	FSGOLD1-36	04035	FSMAN1-36	04016
48"	1200	FSGOLD1-48	04036	FSMAN1-48	04017
60"	1500	FSGOLD1-60	04037	FSMAN1-60	04018
HOOK SIZE; 2-4, U2SP-U3					
24"	600	FSGOLD2-24	04042	FSMAN2-24	04025
36"	900	FSGOLD2-36	04043	FSMAN2-36	04026
48"	1200	FSGOLD2-48	04044	FSMAN2-48	04027
60"	1500	FSGOLD2-60	04045	FSMAN2-60	04028
HOOK SIZE; 4-1/2-7, U4-U7					
24"	600	FSGOLD4-1/2-24	04046	FSMAN4-1/2-24	04030
36"	900	FSGOLD4-1/2-36	04047	FSMAN4-1/2-36	04031
48"	1200	FSGOLD4-1/2-48	04048	FSMAN4-1/2-48	04032
60"	1500	FSGOLD4-1/2-60	04049	FSMAN4-1/2-60	04033

### Manual Roller Lacer®

For customers with lower volume installation, the manual driven Roller Lacer is still available. The belt clamp and face strip innovations noted earlier are standard on this lacer.



www.flexco.com

Australia: 61-2-9680-3322 • England: 44-1274-600-942 • Germany: 49-7428-9406-0 • Mexico: 52-5556-74-53-26 • Republic of South Africa: 27-11-971-2771

**GOODYEAR**  
RUBBER PRODUCTS INC.

Call Toll Free: **1-866-711-4673**  
WebSales@GoodyearRubberProducts.com

**We Ship  
World Wide**