



THORO-SPRAY® EVA Spray Hose Series 7589

EVA tube and cover hose provides good chemical and weather resistance.
4:1 Design factor

>> Weather resistant for exposure to the elements

Tube	Natural EVA
Cover	Natural EVA
Reinforcement	Polyester Yarn
Temperature Range	-50°F to +125°F (-46°C to +52°C)
Branding	PARKER 7589 EVA SPRAY - (SIZE)" – (SIZE) MM - (PRESSURE) PSI WP - MADE IN USA
Brand Description	Ink Brand - Black letter color
Compare to	Kentak EVA; Kuriyama K4350

LENGTHS: 90% of reels contain one continuous length. If two pieces, lengths will be in multiples of 50 ft.

COUPLINGS: For assembly guidelines and coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf.	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7589-375	3/8	9.5	4	0.595	15.1	3.2	5	250
7589-500	1/2	12.7	4	0.720	18.3	3.9	5 1/2	250
7589-750	3/4	19.1	4	1.000	25.4	6.5	7	150
7589-1000	1	25.4	4	1.305	33.1	10.5	10	150

NOTE: Also available in black. Contact IHP Customer Service for more details.

Applications

- Anhydrous Ammonia
- Agricultural
- Lawn
- Chemical Transfer
- Seeder Tubing
- Air and Water Transfer
- Conduit Paint Fluid
- Light Vacuum