



7212-*BK

7212-*BL

7212-*GY

7212-*GN

7212-*RD

7212-*YL

Applications

- Air Tools
- Petroleum Products
- Automotive Plants

JIFFY® HOSE

Push-on Air Hose – MSHA – Silicone Free Series 7212

This oil resistant hose is excellent for use with air tools, to convey water, mild chemicals and various petroleum products. Light, flexible and couples in a jiffy - no clamps or special tools needed. Special braid angle for quick and secure push-on coupling retention. Available in various colors for color coding line. Flame resistant cover is branded with MSHA approval number. **NOTE: Not recommended for impulsing applications. NOTE: Do not use for hot, dry air applications.**

4:1 Design factor

>> Braided reinforcement for superior fitting retention

Tube	Black Nitrile
Cover	Black, blue, gray, green or red Neoprene
Reinforcement	One textile braid
Temperature Range	-40°F to +212°F (-40°C to +100°C)
Branding	PARKER 7212 JIFFY® HOSE PUSH-ON 1/4 in. ID 300 PSI MAX WP MSHA# MADE IN USA B2 (DATE CODE)
Brand Description	Ink Brand - White or black letter color
Compare to	Goodyear Autogrip; Thermoid Flex-Loc 300

LENGTHS: Random lengths on reels. Max 725 ft. min. 400 ft., 5 pieces max. per reel with 50 ft. min. length.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Braid	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Vac. Rating (in. Hg)	Max. Rec. WP
7212-251*	¼	6.4	1	0.500	12.7	9	3.0	28	300
7212-381*	⅜	9.5	1	0.625	15.9	12	3.0	28	300
7212-501*	½	12.7	1	0.750	19.1	15	5.0	28	300
7212-631*	⅝	15.9	1	0.906	23.0	20	6.0	28	300
7212-751*	¾	19.1	1	1.031	26.2	26	7.0	15	300

*To complete part number, add BK (black), BL (blue), GY (gray), GN (green) or RD (red).



WARNING! Do not use clamps with push-on inserts.