



## Hot Tar and Asphalt Hose

### Series 7290

Designed for bulk transfer and delivery of hot petroleum products and hot wax. Will handle full suction and discharge pressures.

4:1 Design factor

#### >> Withstands high temperatures

Tube	Black Nitrile
Cover	Black Neoprene
Reinforcement	Multiple textile plies with helix wire
Temperature Range	-20°F to +350°/400°F (-29°C to +177°/204°C)
Branding	PARKER USA 7290 HOT TAR & ASPHALT HOSE XXX PSI MAX WP 001
Brand Description	Embossed Brand
Compare to	Goodyear Pyroflex; Thermoid Transporter; Boston Black Cat

**LENGTHS:** 100 ft. – other lengths on quotation, contact Customer Service.

**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7290-1500	1½	38.0	4	2.125	54.0	127	4.0	175
7290-2000	2	50.8	4	2.630	66.8	163	6.0	175
7290-3000	3	76.2	4	3.701	94.0	280	12.0	150
7290-4000	4	102.0	4	4.717	119.8	365	16.0	100

7290

### Applications

- Hot Tar
- Commercial Building and Roofing