



Super-Flex FL Fuel Line Hose – CARB Approved

Parker's Super-Flex FL fuel line hose includes a thermoplastic barrier that helps protect the atmosphere from harmful hydrocarbons that escape through the carcass of ordinary fuel hose. This new hose surpasses all of CARB's stringent permeation requirements along with the SAE30R7 specifications. The Super-Flex FL hose also features an abrasion and weather resistant cover to help protect from external application abuse. **NOTE: Approved for biodiesel fuels that meet ASTM D 6751 requirements per UL guidelines for biodiesel compatibility.**

4:1 Design factor

>> Low permeation levels

Tube	NBR with a thermoplastic barrier
Cover	Black Hypalon
Reinforcement	Polyester
Temperature Range	-30°F to +257°F (-34°C to +125°C)
Branding	PARKER 39704 SUPER-FLEX FL ¼" ID LOW PERMEATION FUEL LINE – CARB 2006 APPROVED EXECUTIVE ORDER C-U-06-016
Brand Description	Ink Brand - White letter color
Compare to	Avon Greenbar, Mold-Ex, Mark IV PermaSeal

LENGTHS: Packaged 250 ft. reels, max. 3 pieces. No piece shorter than 25 ft.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series HY, HBL. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

3970x

Part Number	ID (in.)	ID (mm)	Reinf. Braids	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
39703	3/16	4.7	1	0.438	11.1	7.8	1.2	100
39704	¼	6.4	1	0.500	12.7	9.7	1.5	100
39705	5/16	7.9	1	0.562	14.3	11.3	2.0	100
39706	3/8	9.5	1	0.625	15.9	13.0	2.5	100

Applications

- Off road Engines
- Mowers, Blowers, Tillers, Grinders
- Saws
- Pressure Washers