



8341

DAY-LITE®

Suction and Discharge Hose

Series 8341

Designed for wet or dry abrasive product transfer service. The highly abrasion resistant tube is also static conductive, eliminating the need for a static wire. The cover is corrugated for flexible handling. This hose is rated for full suction and discharge. 3:1 Design factor

>> Highly resistant to abrasion

Tube	Natural Rubber / SBR Blend
Cover	Natural Rubber / SBR Blend
Reinforcement	Multiple Polyester Spiral Plies plus Helix Wire
Vacuum Rating	Full Suction
Temperature Range	-40°F to +180°F (-40°C to +82°C)
Branding	Parker 8341 Day-Lite Suction and Discharge Hose Made in USA
Brand Description	Tape Brand - Black letters on green stripe
Compare to	Goodyear Plicord Vacuum

LENGTHS: 50 and 100 ft.; 1½ in. through 4 in. also available in 200 ft. lengths.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling option: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
8341-1500	1½	38.1	2.008	51.0	76.8	4.5	75
8341-2000	2	50.8	2.520	64.0	100.0	6.0	75
8341-3000	3	76.2	3.457	87.8	162.0	9.0	75
8341-4000	4	101.6	4.598	116.8	247.5	12.0	75
8341-6000	6	152.4	6.693	170.0	441.0	18.0	75
8341-8000	8	203.2	8.724	221.0	591.8	24.0	75

Applications

- Sewer Cleaning



WARNING! Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressures.