



# HDW™

## Creamery Washdown Hose

### Series 7080

The HDW Heavy Duty Washdown hose is designed for general washdown and equipment cleaning requirements in food processing, dairy product processing, and industrial plants. The high quality EPDM tube compound allows this hose to be used for 212° F hot water at 300 PSI or saturated steam to +298° F / +148° C at 50 PSI maximum. 4:1 Design factor

#### >> Non-marking cover

Tube	Black high grade EPDM
Cover	White high grade EPDM
Reinforcement	Multiple textile spirals
Temperature Range	-40°F to +212°F @ 300 PSI and to +298°F @ 50 PSI (-40°C to +100°C @ 300 PSI and to +148°C @ 50 PSI)
Branding Example	PARKER SERIES 7080 HDW CREAMERY WASHDOWN 3/4 in. ID (19.1 MM) 300 PSI MAX WP MADE IN USA
Brand Description	Ink Brand - Black letter color
Compare to	Goodyear Plicord Washdown

**LENGTHS:** 350 ft. reels (+50 ft./-0 ft.) are 90% 1 piece, 10% 2 piece, 50 ft. min. length. Also, 50 ft. lengths in cartons are coiled, tied and secured in cartons per order.

**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

7080

#### Applications

- Food Plants
- Dairy



**WARNING!** Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressures.