



# PWD

## High Pressure Washdown Hose

### Series 7143

A premium, flexible and lightweight hose for washdown service in applications such as meat and poultry plants. The specially blended cover provides excellent resistance to animal fats and oils, as well as improved abrasion resistance over similar hose products.

Design factor: 1 Braid = 4:1    2 Braid = 3.5:1

#### >> Fabric reinforcement for kink resistance

Tube	Black synthetic rubber
Cover	Gray (GY) or Yellow (YL) synthetic rubber
Reinforcement	One or two textile braids
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Branding	PARKER SERIES 7143 PWD 3/8 ID (9.5 MM) XXXX PSI MAX WP MADE IN USA (DATE CODE)
Brand Description	Ink Brand - Black letter color
Compare to	Boston Washdown 1250; Gates Cyclone; Goodyear Fortress

**LENGTHS:** Random lengths on 650 ft. nominal reels. 50 ft. min. length.  
Max. 5 pieces.

**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692, 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

7143-YL

7143-GY

#### Applications

- Poultry Plants
- Washdown Service

Part No.	ID (in.)	ID (mm)	Reinf. Braids	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7143-251YL	1/4	6.4	1	0.570	14.5	13	3.0	1000
7143-251GY	1/4	6.4	1	0.570	14.5	13	3.0	1000
7143-381GY	3/8	9.5	1	0.625	15.9	13	4.0	1000
7143-381YL	3/8	9.5	1	0.625	15.9	13	4.0	1000
7143-382GY	3/8	9.5	2	0.734	18.6	19	4.0	1500
7143-382YL	3/8	9.5	2	0.734	18.6	19	4.0	1500



**WARNING!** Not to be used for steam service!