

PARKER/PAGE INTERNATIONAL HOSE

Product Application Guide

Product	Description	Industrial / Paint / Adhesives	Chemical	Semi - Conductor	Cosmetics	Pharm & Biotech	Food & Beverage	Temp Range
PAGE-flex™ SBF SBFW SBFB	Smoothbore, extremely flexible, PFA - silicone - wire - textile composite tube with SS wire braiding standard		●	●	●	●	●	-65°F ~+325°F
PAGE-flex™ SHVW SHVB	Convolute PTFE heavy wall tube - SS wire braiding - true-bore sizing w/helix wire - flare through fitting capable (SHVB conductive ID)	●	●	●				-100°F ~+500°F
PAGE-flex™ PHVW PHVB	Convolute PTFE heavy wall tube - Polypropylene braiding - true-bore sizing w/helix wire - flare through fitting capable (PHVB conductive ID)	●	●	●				0°F ~+212°F
RCTW	Smoothbore flexible FEP tube - wire helix - textile reinforced EPDM cover	●	●	●	●	●	●	-40°F ~+300°F
RCTB	Smoothbore flexible PFA conductive tube - wire helix - textile reinforced EPDM cover	●	●	●	●	●	●	-40°F ~+300°F
STW STB	Smoothbore PTFE tube with SS wire braiding true-bore sizing (STB conductive ID)	●	●	●	●	●	●	-65°F ~+450°F
SSTW SSTB	STW or STB product with Platinum Silicone jacket	●	●	●	●	●	●	-65°F ~+450°F
NCW NCB	Convolute PTFE tube with Nomex braiding true-bore sizing (NCB conductive ID)			●				-100°F ~+400°F
SCW SCB	Convolute PTFE tube with SS wire braiding true-bore sizing (SCB conductive ID)	●	●	●				-100°F ~+500°F
SCWV SCBV	Convolute PTFE heavy wall tube with SS wire braiding true-bore sizing - flare through fitting capable (SCBV conductive ID)	●	●	●				-100°F ~+500°F
PCW PCB	Convolute PTFE tube with polypropylene braiding true-bore sizing (PCB conductive ID)	●	●					0°F ~+212°F
PCWV PCBV	Convolute PTFE heavy wall tube with polypropylene braiding true-bore sizing - flare through fitting capable (PCBV conductive ID)	●	●					0°F ~+212°F
KCW KCB	Convolute PTFE tube with Kynar braiding true-bore sizing (KCB Conductive ID)	●	●	●				-40°F ~+280°F
KCWV KCBV	Convolute PTFE heavy wall tube with Kynar braiding true-bore sizing - flare through fitting capable (KCBV conductive ID)	●	●					-40°F ~+280°F
CWV CBV	Convolute PTFE heavy wall tubing true-bore sizing - flare through fitting capable (CBV Conductive ID)	●	●	●	●	●	●	-100°F ~+500°F
SGT	FEP sight glass tubing	●	●	●	●	●	●	-100°F ~+500°F
SBP	Platinum Silicone textile single braiding hose				●	●	●	-80°F ~+450°F
SWP	Platinum Silicone textile single wrap reinforced hose				●	●	●	-80°F ~+450°F
SWPV	Platinum Silicone textile single wrap reinforced hose w/single helix wire				●	●	●	-80°F ~+450°F
FTHB	Food Grade Rubber Hose with Butyl tube - textile reinforcing - EPDM cover						●	-40°F ~+250°F
FTHN	Food Grade Rubber Hose with Nitrile tube - textile reinforcing - Nitrile cover				●		●	-40°F ~+225°F

Smoothbore
PTFE Hose

Convolute
PTFE Hose

Flare Seal
Hose

Silicone
Hose

Specialty
Hoses

Fittings-Swage

Accessories

Technical
Help

Warranty



Parker Hannifin, Parflex Division



Call Toll Free: 1-866-711-4673

WebSales@GoodyearRubberProducts.com

**We Ship
World Wide**