



# 111HY (HY-MV, HY-MH and HY-MM) Male Ferulok® Flareless - Rigid - Straight (24° Cone w/Nut and Ferrule)



Steel Part Number	Thread Size		Hose I.D.		A		H Hex	W Hex	B	
#										
Hose Fitting	inch		inch		inch	mm	inch	inch	inch	mm
111HY-4-4	7/16x20	-4	1/4	-4	2.42	61	9/16	9/16	1.06	27
111HY-4-6	7/16x20	-4	3/8	-6	2.44	62	3/4	9/16	1.09	28
111HY-5-6	1/2x20	-5	3/8	-6	2.44	62	3/4	5/8	1.09	28
111HY-6-4	9/16x18	-6	1/4	-4	2.44	62	5/8	11/16	1.09	28
111HY-6-6	9/16x18	-6	3/8	-6	2.45	62	11/16	11/16	1.09	28
111HY-8-6	3/4x16	-8	3/8	-6	2.61	66	7/8	7/8	1.25	32
111HY-8-8	3/4x16	-8	1/2	-8	2.72	69	7/8	7/8	1.38	35
111HY-10-8	7/8x14	-10	1/2	-8	2.78	71	1	1	1.44	37
111HY-12-12	1-1/16x12	-12	3/4	-12	3.02	77	1-1/4	1-1/4	1.44	37
111HY-16-16	1-5/16x12	-16	1	-16	3.17	81	1	1-1/2	1.56	40


# 1GJHY (HY-NV) Female Grease Connection - Special PTF Taper Thread - Rigid - Straight - 1/2x27



Steel Part Number	Thread Size		Hose I.D.		A		H Hex	Cutoff Allow. B	
#									
Hose Fitting	inch		inch		inch	mm	inch	inch	mm
1GJHY-8-4	1/2x27	-8	1/4	-4	2.41	61	3/4	1.06	27

# 134HY (HY-RL) Male Standpipe Rigid - Straight (Inch Size Tube O.D.)

Note: 134HY requires the use of Ferrule nut (BU), Ferrule (TU), and Ferulok® Fittings.



Steel Part Number	R		Hose I.D.		A		B	
#								
Hose Fitting	mm		inch		inch	mm	inch	mm
134HY-4-4	1/4	-4	1/4	-4	3.03	77	1.69	43
134HY-6-4	3/8	-6	1/4	-4	3.16	80	1.81	46
134HY-6-6	3/8	-6	3/8	-6	3.17	81	1.81	46
134HY-8-6	1/2	-8	3/8	-6	3.33	85	1.97	50
134HY-8-8	1/2	-8	1/2	-8	3.44	87	2.09	53
134HY-10-8	5/8	-10	1/2	-8	3.66	93	2.31	59
134HY-12-10	3/4	-12	5/8	-10	3.80	97	2.41	61
134HY-12-12	3/4	-12	3/4	-12	3.89	99	2.31	59
134HY-16-16	1	-16	1	-16	4.23	107	2.63	67