



## 129HY (HY-NG) Female Inverted SAE 45° - Rigid - Straight




Steel Part Number	Thread Size		Hose I.D.		A		H Hex	Cutoff Allow. B	
	inch		inch		inch	mm	inch	inch	mm
#									
Hose Fitting	inch		inch		inch	mm	inch	inch	mm
129HY-4-4	7/16x24	-4	1/4	-4	2.16	55	9/16	0.81	21
129HY-5-4	1/2x20	-5	1/4	-5	2.25	57	5/8	0.91	23
129HY-6-6	5/8x18	-6	3/8	-6	2.25	57	7/8	0.91	23

## 1J0HY (HY-OM) Male Seal-Lok™ Rigid - Straight (with O-Ring)



Steel Part Number	Thread Size		Hose I.D.		A		H Hex	Cutoff Allow. B	
	inch		inch		inch	mm	inch	inch	mm
#									
Hose Fitting	inch		inch		inch	mm	inch	inch	mm
1J0HY-4-4	9/16x18	-4	1/4	-4	2.36	60	5/8	1.00	25
1J0HY-6-6	11/16x16	-6	3/8	-6	2.49	63	3/4	1.13	29
1J0HY-8-8	13/16x16	-8	1/2	-8	2.69	68	7/8	1.34	34
1J0HY-12-8	1-3/16x12	-12	1/2	-8	2.91	74	1-1/4	1.56	40

## 1JCHY (HY-OF) Female Seal-Lok™ Swivel - Straight - Short



Steel Part Number	Thread Size		Hose I.D.		A		H Hex	W Hex	B	
	inch		inch		inch	mm	inch	inch	inch	mm
#										
Hose Fitting	inch		inch		inch	mm	inch	inch	inch	mm
1JCHY-4-4	9/16x18	-4	1/4	-4	2.61	66	9/16	11/16	0.94	24
1JCHY-6-6	11/16x16	-6	3/8	-6	2.69	68	11/16	13/16	0.94	24
1JCHY-8-8	13/16x16	-8	1/2	-8	2.91	74	7/8	15/16	1.13	29
1JCHY-12-12	1-3/16x12	-12	3/4	-12	3.31	84	1-1/4	1-3/8	1.13	29