

## Fast-Stor® Air Hose

Fast-Stor® Self Retracting Air Hose, from Parflex, is manufactured from an extremely tough, abrasion resistant nylon. Fast-Stor® hose has excellent memory characteristics over a wide temperature range for long service life in the most rugged applications. The SAFETY YELLOW color of Fast-Stor® is highly desirable due to U.S. Government OSHA directives.

Service temperature range from -40°F to +200°F (-40°C to +93°C).



## How to order: Fast-Stor Assemblies

### Popular Stock Assemblies

| Assembly Part Number | Fast-Stor Hose I. D. | Total Length of Hose ft. | Usable Length ft. | Fitting End #1 | Fitting End #2 Live Swivel | Max. Working Pressure PSI* | Min. Burst at 73°F |
|----------------------|----------------------|--------------------------|-------------------|----------------|----------------------------|----------------------------|--------------------|
| #                    |                      |                          |                   |                |                            |                            |                    |
| A0312-MC4-ML4        | 3/16                 | 12                       | 9                 | 1/4" MPT       | 1/4" MPT                   | 170                        | 680                |
| A0325-MC4-ML4        | 3/16                 | 25                       | 18                | 1/4" MPT       | 1/4" MPT                   | 170                        | 680                |
| A0350-MC4-ML4        | 3/16                 | 50                       | 38                | 1/4" MPT       | 1/4" MPT                   | 170                        | 680                |
| A0412-MC4-ML4        | 1/4                  | 12                       | 9                 | 1/4" MPT       | 1/4" MPT                   | 170                        | 680                |
| A0425-MC4-ML4        | 1/4                  | 25                       | 18                | 1/4" MPT       | 1/4" MPT                   | 170                        | 680                |
| A0450-MC4-ML4        | 1/4                  | 50                       | 38                | 1/4" MPT       | 1/4" MPT                   | 170                        | 680                |
| A0612-MC6-ML6        | 3/8                  | 12                       | 9                 | 3/8" MPT       | 3/8" MPT                   | 170                        | 680                |
| A0625-MC6-ML6        | 3/8                  | 25                       | 18                | 3/8" MPT       | 3/8" MPT                   | 170                        | 680                |
| A0650-MC6-ML6        | 3/8                  | 50                       | 38                | 3/8" MPT       | 3/8" MPT                   | 170                        | 680                |
| A0812-MC8-ML8        | 1/2                  | 12                       | 9                 | 1/2" MPT       | 1/2" MPT                   | 170                        | 680                |
| A0825-MC8-ML8        | 1/2                  | 25                       | 18                | 1/2" MPT       | 1/2" MPT                   | 170                        | 680                |
| A0850-MC8-ML8        | 1/2                  | 50                       | 38                | 1/2" MPT       | 1/2" MPT                   | 170                        | 680                |

### Bulk Hose

| Assembly Part Number | Hose I. D. | Avg. Wall Thick in. | Hose Length ft. | Master Carton Quality | Coil Min. I. D. | Coil Max. O. D. | Max. Working Pressure PSI* | Min. Burst at 73°F |
|----------------------|------------|---------------------|-----------------|-----------------------|-----------------|-----------------|----------------------------|--------------------|
| #                    |            |                     |                 |                       |                 |                 |                            |                    |
| FS-03-100            | 3/16       | .023                | 100             | 600                   | 2.0             | 2.5             | 170                        | 680                |
| FS-04-100            | 1/4        | .030                | 100             | 600                   | 3.0             | 3.7             | 170                        | 680                |
| FS-06-100            | 3/8        | .045                | 100             | 400                   | 4.5             | 5.5             | 170                        | 680                |
| FS-08-100            | 1/2        | .062                | 100             | 400                   | 6.5             | 7.8             | 170                        | 680                |
| FS-12-100            | 3/4        | .075                | 100             | 100                   | 12.0            | 14.0            | 170                        | 680                |

\*Maximum working pressure listed at 75°F or lower and based on safety factor of 4:1 over burst.