



Hydraulic Quick Couplings

General Purpose Couplings 6600 Series

Couplers



Female Thread



| Body Size (in.) | Part No. Steel | Thread Size NPTF | Thread Size ORB | Dimensions (in.) | | | Wt. (LB.) P/Piece |
|-----------------|----------------|------------------|-----------------|------------------|----------|------------------|-------------------|
| | | | | Overall Length | Hex Size | Largest Diameter | |
| | | | | A | B | C | |
| 1/4 | 6601-2-4 | 1/8-27 | — | 1.85 | .88 | 1.08 | 0.27 |
| 1/4 | 6601-4-4 | 1/4-18 | — | 1.85 | .88 | 1.08 | 0.26 |
| 3/8 | 6601-6-6 | 3/8-18 | — | 2.18 | 1.06 | 1.27 | 0.39 |
| 3/8 | 6608-6-6 | — | 9/16-18 | 2.18 | 1.06 | 1.27 | 0.38 |
| 1/2 | 6601-8-10 | 1/2-14 | — | 2.75 | 1.25 | 1.52 | 0.67 |
| 1/2 | 6601-12-10 | 3/4-14 | — | 2.88 | 1.38 | 1.52 | 0.71 |
| 1/2 | 6608-8-10 | — | 3/4-16 | 2.74 | 1.25 | 1.52 | 0.67 |
| 1/2 | 6608-10-10 | — | 7/8-14 | 2.79 | 1.25 | 1.52 | 0.64 |
| 1/2 | 6608-12-10 | — | 1 1/16-12 | 3.01 | 1.38 | 1.52 | 0.77 |
| 3/4 | 6601-12-12 | 3/4-14 | — | 3.36 | 1.62 | 1.90 | 1.31 |
| 3/4 | 6608-12-12 | — | 1 1/16-12 | 3.35 | 1.62 | 1.90 | 1.31 |
| 1 | 6601-16-16 | 1-11 1/2 | — | 4.11 | 1.88 | 2.14 | 0.73 |
| 1 | 6608-16-16 | — | 1 5/16-12 | 4.11 | 1.88 | 2.14 | 1.73 |

Nipples

Female Thread



| Body Size (in.) | Part No. Steel | Thread Size NPTF | Thread Size ORB | Overall Length | Dimensions (in.) | | | Wt. (LB.) P/Piece |
|-----------------|----------------|------------------|-----------------|----------------|------------------|----------|------------------|-------------------|
| | | | | | Exposed* Length | Hex Size | Largest Diameter | |
| | | | | D | E | F | G | |
| 1/4 | 6602-2-4 | 1/8-27 | — | 1.41 | .50 | .56 | .65 | 0.05 |
| 1/4 | 6602-4-4 | 1/4-18 | — | 1.41 | .58 | .75 | .87 | 0.07 |
| 3/8 | 6602-6-6 | 3/8-18 | — | 1.63 | .72 | .88 | 1.01 | 0.11 |
| 3/8 | 6610-6-6 | — | 9/16-18 | 1.63 | .72 | .88 | 1.01 | 0.13 |
| 1/2 | 6602-8-10 | 1/2-14 | — | 2.08 | .78 | 1.06 | 1.23 | 0.21 |
| 1/2 | 6602-12-10 | 3/4-14 | — | 2.30 | .78 | 1.38 | 1.59 | 0.33 |
| 1/2 | 6610-8-10 | — | 3/4-16 | 2.08 | .76 | 1.06 | 1.23 | 0.22 |
| 1/2 | 6610-10-10 | — | 7/8-14 | 2.08 | .82 | 1.12 | 1.30 | 0.21 |
| 1/2 | 6610-12-10 | — | 1 1/16-12 | 2.30 | 1.04 | 1.38 | 1.59 | 0.33 |
| 3/4 | 6602-12-12 | 3/4-14 | — | 2.55 | 1.18 | 1.38 | 1.59 | 0.49 |
| 3/4 | 6610-12-12 | — | 1 1/16-12 | 2.55 | 1.18 | 1.38 | 1.59 | 0.47 |
| 1 | 6602-16-16 | 1-11 1/2 | — | 3.10 | 1.34 | 1.62 | 1.88 | 0.75 |
| 1 | 6610-16-16 | — | 1 5/16-12 | 3.10 | 1.34 | 1.62 | 2.17 | 0.72 |

* This dimension represents the portion that is exposed when the nipple is inserted into the mating parker Coupler.

Replacement Parts

6600 Series

| Body Size (in.) | 1/4 | 3/8 | 1/2 | 3/4 | 1 |
|------------------|---------------|---------------|---------------|----------------|---------------|
| O-Rings - Buna N | 2-112N0674-70 | 2-115N0674-70 | 2-211N0674-70 | 2-123NN0674-70 | 2-126N0674-70 |
| Back-up Rings | 4118006 | 4118005 | 50-140-4 | 4138001 | 4148002 |

B Hydraulics

Quick Coupling Division