



Features

- Meets or exceeds ISO 16028 specification design and test requirements.
- Wider size variations and increased pressures over FE couplers.
- ISO-16028 Interface for universal interchangeability.
- Modular design for increased flexibility with fitting port options.
- Brinell relief on male half to increase life and resist wear.
- Induction hardened locking surface to resist brinelling, damage and abuse.
- Heat Treated components to resist scratches and wear.
- Smooth flow path for low pressure drop.
- Heavy locking collar to resist damage and abuse.
- Anti-blowout Nitrile and BFT male half seal prevents damage and premature failure with residual system pressure.
- Optional Color coding bands for system identification.
- Crimped valve seal prevents seal washout.
- Steel guide to resist damage on breaker applications.
- Push-to-connect locking mechanism.
- Optional sleeve lock.

Specifications

Body Size (in.)	1/4	3/8	1/2	5/8	3/4	1
Rated Pressure (PSI)	4568	3625	3625	3625	3625	2900
Rated Flow (GPM)	3	6	12	20	26	50
Temperature Range (std.seals)	-40 to +250° F					
Spillage (ML) (max. per disconnect)	0.015	0.015	0.020	0.030	0.150	0.200
Air Inclusion (ML) (max. per connect)	0.020	0.020	0.070	0.070	0.100	0.150

Applications

Parker FEM Series couplings are designed to meet the stringent design and pressure requirements of ISO 16028. The FEM modular design also facilitates wider variations in fitting options. Parker FEM couplers are designed for use in the construction, utility and agricultural equipment markets. As with all Parker flush-face designs the non-spill feature eliminates hydraulic spillage and air inclusion when connecting or disconnecting hydraulic attachments. The FEM Series is also ideal for many other applications where hydraulic spillage is a concern and global interchangeability with other manufacturers is important.

Materials of Construction

- Body:** Steel
- Finish:** Zinc plated with yellow chromate finish
- Valve:** Flush face valving
- Seal:** Anti blow-out NBR Nitrile with BFT seal (male only)

Performance

