


CC870MLO**Full Dimensions**

Long 90° Metric Straight Thread Elbow
ORFS-Long / ISO 6149

ISO 8434-3 SDEL
SAE 52M1587




* S2 – Across
Hex Flats

TUBE FITTING PART #	END SIZE			L7 (mm)	L29 (mm)	S2 (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)	
	1		2				S	SS
	(mm)	(in.)	ISO 261					
4M12CC87OMLO	6	1/4	M12X1.5	21.5	56.4	14		
6M14CC87OMLO	8,10	3/8	M14X1.5	25	56.4	19		
8M18CC87OMLO	12	1/2	M18X1.5	28	74.9	22	6.0	
10M22CC87OMLO	14,15,16	5/8	M22X1.5	33.5	87.9	27	6.0	
12M27CC87OMLO	18,20	3/4	M27X2	37.5	100.5	27	6.0	
16M33CC87OMLO	22,25	1	M33X2	41.5	114.5	36		

C80MLO**Full Dimensions**

Metric Straight Thread Elbow
ORFS / Metric-ORR



* S2 – Across
Hex Flats

TUBE FITTING PART #	END SIZE			L7 (mm)	L10 (mm)	S2 (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)	
	1		2				S	SS
	(mm)	(in.)	ISO 261					
4M12C8OMLO	6	1/4	M12X1.5	21.5	33	14	3.6	
6M12C8OMLO	8, 10	3/8	M12X1.5	25	35.5	17	3.6	
6M14C8OMLO	8, 10	3/8	M14X1.5	25	35.5	17	3.6	
6M16C8OMLO	8, 10	3/8	M16X1.5	25	37.5	17	3.6	
8M14C8OMLO	12	1/2	M14X1.5	28	36	19		
8M18C8OMLO	12	1/2	M18X1.5	28	41	19	3.6	
8M22C8OMLO	12	1/2	M22X1.5	31.5	49	27	3.6	
10M22C8OMLO	14, 15, 16	5/8	M22X1.5	33.5	49	27	3.6	
12M27C8OMLO	18, 20	3/4	M27X2	37.5	55.5	30	3.6	
16M33C8OMLO	22, 25	1	M33X2	41.5	59.5	36		
20M38C8OMLO	28, 30, 32	1 1/4	M38X2	44.5	62	41		
20M42C80MLO	28, 30, 32	1 1/4	M42X2	44.5	63	41	2.5	

Dimensions and pressures for reference only, subject to change.