




Seal-Lok Lite O-Ring Face Seal Tube Ends




Seal-Lok Lite Male



Seal-Lok Lite Swivel Assembly



Seal-Lok Lite Tube End



Seal-Lok Lite WLL Body

SAE Dash Size	Tube O.D.		Thread	Tube Nut Hex	Swivel Nut Hex	Bulkhead Locknut Hex	Nominal Drill	Nominal Drill Swivel End	Max Bulkhead Thickness	Tube Nut Assembled Allowance	Swivel Turn Back	Male Turn Back	Bulkhead			Across Corners	
													Locknut Thickness	Pilot Dia	Length	Tube Nut Hex	Swivel Nut Hex
	(in.)	(mm)	T Metric Thread	C (in.)	C2 (in.)	C3 (in.)	D (in.)	D1 (in.)	E (in.)	F (in.)	L1 (in.)	L4 (in.)	R (in.)	W (in.)	WW (in.)	U1 (in.)	U2 (in.)
6	3/8	8 10	M18X1.5	3/4	13/16	1	0.323	0.323	0.50	0.247	0.560	0.285	0.23	0.708	1.05	0.91	1.15
8	1/2	12	M22X1.5	15/16	15/16	1 1/8	0.453	0.453	0.50	0.267	0.590	0.301	0.23	0.866	1.06	1.04	1.29
12	3/4	18 20	M30X1.5	1 1/4	1 5/16	1 1/2	0.766	0.766	0.50	0.331	0.650	0.309	0.39	1.181	1.23	1.41	1.73
16	1	25	M36X1.5	1 5/8	1 5/8	1 3/4	0.953	0.953	0.50	0.426	0.805	0.396	0.41	1.417	1.34	1.81	2.01

1) Recommended clearance hole = $W + 0.015$.

2) See [page O9](#) for Seal-Lok Lite O-rings.

Dimensions and pressures for reference only, subject to change.