




HLLO**Full Dimensions**Union
SLL/SLL


TUBE FITTING PART #	END SIZE		H (in.)	FF (in.)	STANDARD Dynamic Pressure (x 1,000 PSI) -SS N0674
	1 (in.)	2 (in.)			
6 HLLO	3/8	3/8	3/4	0.82	1.5
8 HLLO	1/2	1/2	15/16	0.86	1.5
8-6 HLLO	1/2	3/8	15/16	0.84	1.5
12 HLLO	3/4	3/4	1 1/4	1.03	1.5
16 HLLO	1	1	1 1/2	1.27	1.5

LLOT1**Full Dimensions**Seal-Lok Lite/
Flareless Tube Stub


TUBE FITTING PART #	TUBE O.D. (in.)	DD (in.)	E DIA. (in.)	H HEX (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI) -SS N0674
6 LLOT1	3/8	0.73	3/8	3/4	1.22	1.5
8 LLOT1	1/2	1.00	1/2	15/16	1.50	1.5
12 LLOT1	3/4	1.03	3/4	1 1/4	1.56	1.5
16 LLOT1	1	1.36	1	1 1/2	2.01	1.5

WLLO**Full Dimensions**Bulkhead Union
SLL/SLLWLLO-WLLNL – Body with locknut
(See [page B7](#) for WLLNL)

TUBE FITTING PART #	END SIZE		B HEX (in.)	E MAX. BULKHEAD (in.)	GG (in.)	SS (in.)	W DIA. (mm)	WW (in.)	STANDARD Dynamic Pressure (x 1,000 PSI) -SS N0674
	1 (in.)	2 (in.)							
6 WLLO	3/8	3/8	1	0.5	1.58	0.06	18	1.05	1.5
8 WLLO	1/2	1/2	1 1/8	0.5	1.61	0.06	22	1.06	1.5
12 WLLO	3/4	3/4	1 1/2	0.5	1.95	0.06	30	1.23	1.5
16 WLLO	1	1	1 3/4	0.5	2.21	0.06	36	1.34	1.5

F5OLLO**Full Dimensions**Straight Thread Connector
Seal-Lok Lite/SAE-ORB

TUBE FITTING PART #	END SIZE		H HEX (in.)	L5 (in.)	STANDARD Dynamic Pressure (x 1,000 PSI) -SS N0674
	1 (in.)	2 UN/UNF-2A			
6 F5OLLO	3/8	9/16-18	3/4	0.96	1.5
8 F5OLLO	1/2	3/4-16	15/16	0.98	1.5
12 F5OLLO	3/4	1 1/16-12	1 1/4	1.26	1.5
16 F5OLLO	1	1 5/16-12	1 1/2	1.41	1.5

FLLO**Full Dimensions**Seal-Lok Lite/
PTF-Short

TUBE FITTING PART #	END SIZE		H HEX (in.)	FF (in.)	STANDARD Dynamic Pressure (x 1,000 PSI) -SS N0674
	1 (in.)	2 PTF			
6 FLLO	3/8	1/4-18	3/4	1.06	1.5
6-6 FLLO	3/8	3/8-18	3/4	1.06	1.5
8 FLLO	1/2	3/8-18	7/8	1.08	1.5
12 FLLO	3/4	3/4-14	1 1/4	1.40	1.5
16 FLLO	1	1-11 1/2	1 1/2	1.71	1.5

Dimensions and pressures for reference only, subject to change.