



F4OMX Full DimensionsMale Connector – BSPP
37° Flare / BSPP-ORR


TUBE FITTING PART #	END SIZE			C4 (mm)	L5 (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1		2			-S	-SS	-B
	(mm)	(in.)	BSPP					
4F4OMX	6	1/4	1/8-28	17	28.7	5.0		
4-4F4OMX	6	1/4	1/4-19	19	32.0	5.0		
4-6F4OMX	6	1/4	3/8-19	22	33.0	5.0		
4-8F4OMX	6	1/4	1/2-14	30	38.6	5.0		
5-4F4OMX	8	5/16	1/4-19	19	32.0	5.0		
5-6F4OMX	8	5/16	3/8-19	22	33.0	5.0		
6F4OMX	10	3/8	1/4-19	19	32.0	5.0		
6-6F4OMX	10	3/8	3/8-19	22	33.0	5.0		
6-8F4OMX	10	3/8	1/2-14	30	38.6	5.0		
8-4F4OMX	12	1/2	1/4-19	19	35.0	5.0		
8F4OMX	12	1/2	3/8-19	22	36.0	5.0		
8-8F4OMX	12	1/2	1/2-14	30	41.4	5.0		
8-12F4OMX	12	1/2	3/4-14	36	42.4	4.0		
10-6F4OMX	14, 15, 16	5/8	3/8-19	24	39.1	5.0		
10F4OMX	14, 15, 16	5/8	1/2-14	30	43.9	5.0		
12-8F4OMX	18, 20	3/4	1/2-14	30	46.7	5.0		
12F4OMX	18, 20	3/4	3/4-14	36	47.5	4.0		
12-16F4OMX	18, 20	3/4	1-11	46	52.6	4.0		
16-12F4OMX	25	1	3/4-14	36	48.5	4.0		
16F4OMX	25	1	1-11	46	53.6	4.0		
16-20F4OMX	25	1	1 1/4-11	50	55.1	3.6		
20F4OMX	30, 32	1 1/4	1 1/4-11	50	56.9	3.6		
24-20F4OMX	38	1 1/2	1 1/4-11	50	60.4	3.0		
24F4OMX	38	1 1/2	1 1/2-11	55	61.0	3.0		

Note: If F4OMX is not available, use F42EDMX.


F3MX Full DimensionsMale Connector – BSPT
37° Flare / BSPT

TUBE FITTING PART #	END SIZE			C HEX (mm)	L (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1		2			-S	-SS	-B
	(mm)	(in.)	BSPT					
4F3MX	6	1/4	1/8-28	13	31.0	4.5		
4-4F3MX	6	1/4	1/4-19	14	36.0	4.5		
5F3MX	8	5/16	1/8-28	14	31.0	4.5		
5-4F3MX	8	5/16	1/4-19	14	36.0	4.5		
6F3MX	10	3/8	1/4-19	16	36.3	4.5		
6-6F3MX	10	3/8	3/8-19	19	36.4	4.5		
6-8F3MX	10	3/8	1/2-14	22	42.9	4.5		
8-4F3MX	12	1/2	1/4-19	19	38.9	4.5		
8F3MX	12	1/2	3/8-19	19	38.9	4.5		
8-8F3MX	12	1/2	1/2-14	22	45.5	4.5		
10-6F3MX	14, 15, 16	5/8	3/8-19	24	43.2	4.5		
10F3MX	14, 15, 16	5/8	1/2-14	24	48.0	4.5		
10-12F3MX	14, 15, 16	5/8	3/4-14	27	49.5	2.3		
12-8F3MX	18, 20	3/4	1/2-14	27	52.3	4.5		
12F3MX	18, 20	3/4	3/4-14	27	52.3	2.3		
12-16F3MX	18, 20	3/4	1-11	36	57.1	2.3		
16-12F3MX	25	1	3/4-14	36	53.6	2.3		
16F3MX	25	1	1-11	36	58.4	2.3		
20-16F3MX	30, 32	1 1/4	1-11	46	61.4	2.3		
20F3MX	30, 32	1 1/4	1 1/4-11	46	62.2	2.3		
24F3MX	38	1 1/2	1 1/2-11	50	68.1	2.3		

Dimensions and pressures for reference only, subject to change.

G4MX Full DimensionsFemale Connector – BSPP
37° Flare / BSPP

TUBE FITTING PART #	END SIZE			C1 (mm)	L2 (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1		2			S	SS	B
	(mm)	(in.)	BSPP					
4G4MX	6	1/4	1/8-28	16	30.2	5.0		
4-4G4MX	6	1/4	1/4-19	19	35.3	5.0		
5G4MX	8	5/16	1/8-28	16	29.7	5.0		
6G4MX	10	3/8	1/4-19	19	35.6	5.0		
6-6G4MX	10	3/8	3/8-19	22	37.1	5.0		
8G4MX	12	1/2	3/8-19	22	39.6	5.0		
8-8G4MX	12	1/2	1/2-14	30	45.5	5.0		
10G4MX	14, 15, 16	5/8	1/2-14	30	48.0	5.0		
12G4MX	18, 20	3/4	3/4-14	36	52.3	4.0		
16G4MX	25	1	1-11	46	59.7	4.0		

HX6 Full DimensionsSwivel Nut Union
37° Swivel / 37° Swivel

HPD Base # 0606

TUBE FITTING PART #	END SIZE	C4 HEX (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1 & 2 (in.)			-S	-SS	-B
4 HX6	1/4	9/16	1.48	7.5	7.5	
6 HX6	3/8	11/16	1.75	6.0		
8 HX6	1/2	7/8	2.02	6.0		
10 HX6	5/8	1	2.24	5.0		
12 HX6	3/4	1 1/4	2.43	5.0		
16 HX6	1	1 1/2	2.68	4.0		

Visual
IndexHow To
Order

Specs

Assembly /
Installation3-D
CAD
ModelReference
Section