


JTXO Full Dimensions


Union Tee
37° Flare (all three ends)



TUBE FITTING PART #	END SIZE	M (in.)	M1 (in.)	M2 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI) -SS
	1 - 3 (in.)					
4 JTXO	1/4	0.90	0.90	0.90	7/16	7.7
6 JTXO	3/8	1.08	1.08	1.08	9/16	6.0
8 JTXO	1/2	1.25	1.25	1.25	3/4	6.0
10 JTXO	5/8	1.50	1.50	1.50	7/8	5.0
12 JTXO	3/4	1.70	1.70	1.70	1 1/16	5.0
16 JTXO	1	1.89	1.89	1.89	1 5/16	5.0
20 JTXO	1 1/4	2.13	2.13	2.13	1 5/8	5.0
24 JTXO	1 1/2	2.41	2.41	2.41	1 7/8	5.0

RTXO Full Dimensions


Male Run Tee
37° Flare / NPTF / 37° Flare



TUBE FITTING PART #	END SIZE		M (in.)	N (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI) -SS
	1 & 3 (in.)	2 NPTF				
4 RTXO	1/4	1/8-27	0.90	0.78	7/16	6.0
6 RTXO	3/8	1/4-18	1.08	1.09	9/16	6.0
8 RTXO	1/2	3/8-18	1.25	1.22	3/4	6.0
10 RTXO	5/8	1/2-14	1.51	1.47	7/8	5.0
12 RTXO	3/4	3/4-14	1.70	1.59	1 1/16	4.0
16 RTXO	1	1-11 1/2	1.89	1.97	1 5/16	3.0
20 RTXO	1 1/4	1 1/4-11 1/2	2.13	2.38	1 5/8	2.5
24 RTXO	1 1/2	1 1/2-11 1/2	2.41	2.64	1 7/8	2.5

R5OXO Full Dimensions

Straight Thread Run Tee
37° Flare / SAE-ORB / 37° Flare



TUBE FITTING PART #	END SIZE		M (in.)	M7 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI) -SS
	1 (in.)	2 UN/UNF-2A				
4 R5OXO	1/4	7/16-20	0.90	1.03	7/16	6.0
6 R5OXO	3/8	9/16-18	1.08	1.25	9/16	5.4
8 R5OXO	1/2	3/4-16	1.25	1.45	3/4	5.4
10 R5OXO	5/8	7/8-14	1.51	1.70	7/8	5.4
12 R5OXO	3/4	1 1/16-12	1.70	1.94	1 1/16	5.4
16 R5OXO	1	1 5/16-12	1.89	2.05	1 5/16	3.7
20 R5OXO	1 1/4	1 5/8-12	2.13	2.25	1 5/8	2.8

Dimensions and pressures for reference only, subject to change.

Visual
IndexHow To
Order

Specs

Assembly /
Installation3-D
CAD
ModelReference
Section