


GBU Full Dimensions

Female Connector
Flareless / NPTF

SAE 080103




TUBE FITTING PART #	END SIZE		C1 HEX (in.)	L2 (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)	
	1	2			-S	-SS
	(in.)	NPTF				
2 GBU	1/8	1/8-27	9/16	1.05	5.0	
4 GBU	1/4	1/8-27	9/16	1.09	5.0	5.0
4-4 GBU	1/4	1/4-18	3/4	1.29	5.0	5.0
5 GBU	5/16	1/8-27	9/16	1.08	5.0	
6 GBU	3/8	1/4-18	3/4	1.31	5.0	5.0
6-6 GBU	3/8	3/8-18	7/8	1.34	5.0	5.0
6-8 GBU	3/8	1/2-14	1 1/8	1.59	5.0	5.0
8 GBU	1/2	3/8-18	7/8	1.47	5.0	5.0
8-4 GBU	1/2	1/4-18	7/8	1.46	5.0	5.0
8-8 GBU	1/2	1/2-14	1 1/8	1.69	5.0	5.0
10 GBU	5/8	1/2-14	1 1/8	1.77	4.5	4.5
12 GBU	3/4	3/4-14	1 3/8	1.89	4.0	4.0
14 GBU	7/8	3/4-14	1 3/8	1.86	3.0	
16 GBU	1	1-11 1/2	1 5/8	2.13	3.0	3.0
20 GBU	1 1/4	1 1/4-	2	2.22	2.5	
24 GBU	1 1/2	1 1/2-	2 3/8	2.23	2.5	

TRBU Full Dimensions

Tube End Reducer
Tube / Flareless

SAE 080123




TUBE FITTING PART #	END SIZE		C HEX (in.)	L (in.)	Q (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)	
	1	2				-S	-SS
	(in.)	(in.)					
6-4 TRBU	3/8	1/4	1/2	1.61	0.88	6.0	6.0
8-4 TRBU	1/2	1/4	9/16	1.73	1.00	5.0	5.0
8-6 TRBU	1/2	3/8	5/8	1.77	1.00	5.0	5.0
10-6 TRBU	5/8	3/8	11/16	1.86	1.09	5.0	
10-8 TRBU	5/8	1/2	13/16	1.95	1.09	4.5	4.5
12-6 TRBU	3/4	3/8	13/16	1.94	1.16	4.5	4.5
12-8 TRBU	3/4	1/2	13/16	2.03	1.16	4.5	4.5
12-10 TRBU	3/4	5/8	15/16	2.16	1.16	4.5	
14-10 TRBU	7/8	5/8	15/16	2.14	1.16	4.0	
16-8 TRBU	1	1/2	1 1/16	2.05	1.13	4.0	4.0
16-10 TRBU	1	5/8	1 1/16	2.11	1.13	4.0	
16-12 TRBU	1	3/4	1 1/8	2.25	1.13	4.0	4.0
20-16 TRBU	1 1/4	1	1 3/8	2.28	1.16	3.0	
24-12 TRBU	1 1/2	3/4	1 5/8	2.45	1.25	2.0	
24-16 TRBU	1 1/2	1	1 5/8	2.45	1.25	2.0	
24-20 TRBU	1 1/2	1 1/4	1 7/8	2.45	1.25	2.0	

V5BU Full Dimensions

45° Straight Thread Elbow
Flareless / SAE-ORB

SAE 080320




* Y – Across wrench flats

TUBE FITTING PART #	END SIZE		M2 (in.)	M8 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)	
	1	2				-S	-SS
	(in.)	UN/UNF-2A					
4 V5BU	1/4	7/16-20	0.70	1.05	7/16	5.0	5.0
6 V5BU	3/8	9/16-18	0.83	1.14	9/16	5.0	5.0
8 V5BU	1/2	3/4-16	0.98	1.30	3/4	5.0	
12 V5BU	3/4	1 1/16-12	1.27	1.73	1 1/16	4.0	
16 V5BU	1	1 5/16-12	1.36	1.86	1 5/16	3.0	

VBU Full Dimensions

45° Male Elbow
Flareless / NPTF

SAE 080302



* Y – Across wrench flats

TUBE FITTING PART #	END SIZE		M2 (in.)	N2 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)	
	1	2				-S	-SS
	(in.)	NPTF					
3 VBU	3/16	1/8-27	0.64	0.53	7/16	5.0	
4 VBU	1/4	1/8-27	0.70	0.64	7/16	5.0	5.0
4-4 VBU	1/4	1/4-18	0.81	0.86	9/16	5.0	
5 VBU	5/16	1/8-27	0.75	0.66	9/16	5.0	
6 VBU	3/8	1/4-18	0.83	0.86	9/16	5.0	5.0
8 VBU	1/2	3/8-18	0.98	0.95	3/4	5.0	5.0
10 VBU	5/8	1/2-14	1.08	1.17	7/8	4.5	4.5
12 VBU	3/4	3/4-14	1.27	1.20	1 1/16	4.0	
14 VBU	7/8	3/4-14	1.34	1.30	1 5/16	3.0	
16 VBU	1	1-11 1/2	1.36	1.48	1 5/16	3.0	
20 VBU	1 1/4	1 1/4-11 1/2	1.45	1.67	1 5/8	2.5	

Dimensions and pressures for reference only, subject to change.