


EBU Full Dimensions

Union Elbow
Flareless / Flareless

SAE 080201




* Y – Across wrench flats

TUBE FITTING PART #	END SIZE		M (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)	
	1 (in.)	2 (in.)			-S	-SS
2 EBU	1/8	1/8	0.78	7/16	5.0	
4 EBU	1/4	1/4	0.89	7/16	5.0	5.0
5 EBU	5/16	5/16	0.95	9/16	5.0	
6 EBU	3/8	3/8	1.05	9/16	5.0	5.0
8 EBU	1/2	1/2	1.25	3/4	5.0	5.0
10 EBU	5/8	5/8	1.42	7/8	4.5	4.5
12 EBU	3/4	3/4	1.58	1 1/16	4.0	4.0
14 EBU	7/8	7/8	1.66	1 5/16	3.0	
16 EBU	1	1	1.73	1 5/16	3.0	3.0
20 EBU	1 1/4	1 1/4	1.89	1 5/8	2.5	
24 EBU	1 1/2	1 1/2	2.02	1 7/8	2.0	2.0
32 EBU	2	2	2.45	2 1/2	1.5	

WEBU Full Dimensions

Bulkhead Union Elbow
Flareless / Flareless Bulkhead




* Y – Across wrench flats.
W** – Bulkhead pilot dia. recommended
clearance hole is +.015 over W dia.

TUBE FITTING PART #	END SIZE		I2 (in.)	M3 (in.)	M4 (in.)	W DIA (in.)	Y (in.)	Max. Bulkhead Thickness	STANDARD Dynamic Pressure (x 1,000 PSI)	
	1 (in.)	2 (in.)							-S	-SS
6 WEBU	3/8	3/8	0.98	1.08	1.7	0.56	9/16	0.26	5.0	
8 WEBU	1/2	1/2	1.12	1.33	1.97	0.75	3/4	0.30	5.0	

C6BU Full Dimensions

Swivel Nut Elbow
Flareless / Flareless Swivel

SAE 080221




* Y – Across wrench flats

TUBE FITTING PART #	END SIZE		M (in.)	M5 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)	
	1 (in.)	2 (in.)				-S	-SS
4 C6BU	1/4	1/4	0.89	1.00	7/16	5.0	5.0
6 C6BU	3/8	3/8	1.05	1.25	9/16	5.0	5.0
8 C6BU	1/2	1/2	1.25	1.38	3/4	5.0	5.0
10 C6BU	5/8	5/8	1.42	1.62	7/8	4.5	
12 C6BU	3/4	3/4	1.58	1.75	1 1/16	4.0	4.0
16 C6BU	1	1	1.73	2.00	1 5/16	3.0	
20 C6BU	1 1/4	1 1/4	1.89	2.31	1 5/8	2.5	

C5BU Full Dimensions

Straight Thread Elbow
Flareless / SAE-ORB

SAE 080220



* Y – Across wrench flats

TUBE FITTING PART #	END SIZE		M (in.)	M7 (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)	
	1 (in.)	2 UN/UNF-2A				-S	-SS
3 C5BU	3/16	3/8-24	0.84	0.94	7/16	5.0	5.0
4 C5BU	1/4	7/16-20	0.89	1.03	7/16	5.0	5.0
5 C5BU	5/16	1/2-20	0.95	1.13	9/16	5.0	5.0
6 C5BU	3/8	9/16-18	1.05	1.25	9/16	5.0	5.0
6-8 C5BU	3/8	3/4-16	1.14	1.45	3/4	5.0	
8 C5BU	1/2	3/4-16	1.25	1.45	3/4	5.0	5.0
8-6 C5BU	1/2	9/16-18	1.27	1.33	3/4	5.0	
8-10 C5BU	1/2	7/8-14	1.34	1.70	7/8	4.5	
8-12 C5BU	1/2	1 1/16-12	1.43	1.94	1 1/16	4.0	
10 C5BU	5/8	7/8-14	1.42	1.70	7/8	4.5	4.5
12 C5BU	3/4	1 1/16-12	1.58	1.94	1 1/16	4.0	4.0
12-8 C5BU	3/4	3/4-16	1.58	1.63	1 1/16	4.0	
12-10 C5BU	3/4	7/8-14	1.58	1.78	1 1/16	4.0	
12-16 C5BU	3/4	1 5/16-12	1.73	2.05	1 5/16		
16 C5BU	1	1 5/16-12	1.73	2.05	1 5/16	3.0	3.0
16-12 C5BU	1	1 1/16-12	1.73	2.05	1 5/16	3.0	
20 C5BU	1 1/4	1 5/8-12	1.89	2.25	1 5/8	2.5	
24 C5BU	1 1/2	1 7/8-12	2.02	2.39	1 7/8	2.0	2.0
32 C5BU	2	2 1/2-12	2.45	2.89	2 1/2	1.5	

Dimensions and pressures for reference only, subject to change.