



OBI2 Full DimensionsFemale Branch Tee
Intru-Lok / NPTF


Y* – Across wrench flats

TUBE FITTING PART #	END SIZE			M1 (in.)	N1 (in.)	Y1 (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)
	1	2	3				-B
	(in.)	(in.)	NPTF				
4 OBI2	1/4	1/4	1/8-27	0.72	0.53	9/16	1.5
4-4-4 OBI2	1/4	1/4	1/4-18	0.86	0.69	3/4	1.5
6 OBI2	3/8	3/8	1/4-18	0.92	0.69	3/4	1.5
8 OBI2	1/2	1/2	3/8-18	1.09	0.81	7/8	1.5

MBI2 Full DimensionsFemale Run Tee
Intru-Lok / NPTF / Intru-Lok


Y* – Across wrench flats

TUBE FITTING PART #	END SIZE			M1 (in.)	N1 (in.)	Y1 (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)
	1	2	3				-B
	(in.)	(in.)	NPTF				
4 OBI2	1/4	1/4	1/8-27	0.72	0.53	9/16	1.5
4-4-4 OBI2	1/4	1/4	1/4-18	0.86	0.69	3/4	1.5
6 OBI2	3/8	3/8	1/4-18	0.92	0.69	3/4	1.5
8 OBI2	1/2	1/2	3/8-18	1.09	0.81	7/8	1.5

KBI2 Full DimensionsUnion Cross
Intru-Lok (all four ends)


Y* – Across wrench flats

TUBE FITTING PART #	END SIZE				M (in.)	Y (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)
	1 (in.)	2 (in.)	3 (in.)	4 (in.)			-B
	4 KBI2	1/4	1/4	1/4			1/4
6 KBI2	3/8	3/8	3/8	3/8	0.78	1/2	1.5


T22I
Mountie

Typical application

TUBE FITTING PART #	TUBE O.D. (in.)	T TUBE END UN/UNF-2A	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)
4 T22I	1/4	1/4-20	0.81	1.5
6 T22I	3/8	1/4-20	0.81	1.5

PNI Full DimensionsPlug
Intru-Lok

TUBE FITTING PART #	TUBE O.D. (in.)	T TUBE END UN/UNF-2A	C HEX (in.)	L3 (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)
4 PNI	1/4	7/16-20	7/16	0.5	1.5
5 PNI	5/16	1/2-20	1/2	0.52	1.5
6 PNI	3/8	9/16-18	9/16	0.59	1.5
8 PNI	1/2	3/4-16	3/4	0.67	1.5

FNI
Cap
Intru-Lok

TUBE FITTING PART #	TUBE O.D. (in.)	C HEX (in.)	L5 (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)
2 FNI	1/8	3/8	0.36	1.5
3 FNI	3/16	7/16	0.34	1.5
4 FNI	1/4	1/2	0.44	1.5
5 FNI	5/16	9/16	0.45	1.5
6 FNI	3/8	5/8	0.45	1.5
8 FNI	1/2	7/8	0.58	1.5

Dimensions and pressures for reference only, subject to change.

Visual
IndexHow To
Order

Specs

Assembly /
InstallationReference
Section