


G Full Dimensions

Union

24° Flareless / 24° Flareless




TUBE FITTING PART #	END SIZE		I 1 (mm)	S1 (mm)	STANDARD Pressure Rating (bar)				
	1 (mm)	2 (mm)			EO				EO-2
					CF	71	MS	CF	71
G04LL	4	4	12	9	100	100	63	100	
G06LL	6	6	9	11	100	100	63	100	
G08LL	8	8	12	12	100	100	63		
G10LL	10	10	12	14	100		63		
G12LL	12	12	11	17	100				
G06L	6	6	10	12	315	315	200	315	315
G08L	8	8	11	14	315	315	200	315	315
G10L	10	10	13	17	315	315	200	315	315
G12L	12	12	14	19	315	315	200	315	315
G15L	15	15	16	24	315	315	200	315	315
G18L	18	18	16	27	315	315	200	315	315
G22L	22	22	20	32	160	160	100	160	160
G28L	28	28	21	41	160	160	100	160	160
G35L	35	35	20	46	160		100	160	160
G42L	42	42	21	55	160		100	160	160
G06S	6	6	16	14	630	630	400	630	630
G08S	8	8	18	17	630	630	400	630	630
G10S	10	10	17	19	630	630	400	630	
G12S	12	12	19	22	630	630	400	630	630
G14S	14	14	22	24	630		400	630	
G16S	16	16	21	27	400	400	250	400	400
G20S	20	20	23	32	400	400	250	400	400
G25S	25	25	26	41	400	400	250	400	
G30S	30	30	27	46	400	400	250	400	400
G38S	38	38	29	55	315		205	315	315

For EO-2 part number, insert "Z" between size and pressure series. Example: G06ZLCF

GR Full Dimensions

Union Reducer

24° Flareless / 24° Flareless



TUBE FITTING PART #	END SIZE		I 1 (mm)	S1 (mm)	STANDARD Pressure Rating (bar)				
	1 (mm)	2 (mm)			EO				EO-2
					CF	71	MS	CF	71
GR06/04LL	6	4	10.5	11	100				
GR08/04LL	8	4	12.5	12	100				
GR08/06LL	8	6	11.0	12	100				
GR08/06L	8	6	11.0	14	315	315		315	315
GR10/06L	10	6	12.0	17	315	315		315	
GR10/08L	10	8	12.0	17	315	315		315	
GR12/06L	12	6	13.0	19	315			315	
GR12/08L	12	8	13.0	19	315			315	
GR12/10L	12	10	14.0	19	315	315		315	
GR15/10L	15	10	15.0	24	315	315			
GR15/12L	15	12	15.0	24	315	315		315	
GR18/10L	18	10	15.5	27	315	315		315	
GR18/12L	18	12	15.5	27	315	315		315	
GR18/15L	18	15	16.5	27	315			315	
GR22/12L	22	12	17.5	32	160			160	
GR22/15L	22	15	18.5	32	160			160	160
GR22/18L	22	18	18.0	32	160	160		160	
GR28/18L	28	18	19.0	41	160			160	
GR28/22L	28	22	21.0	41	160	160		160	
GR35/22L	35	22	21.0	46	160			160	
GR35/28L	35	28	21.0	46	160				
GR08/06S	8	6	18.0	17	630				
GR10/06S	10	6	17.5	19	630				
GR10/08S	10	8	17.5	19	630				
GR12/06S	12	6	19.5	22	630			630	
GR12/08S	12	8	19.5	22	630			630	
GR12/10S	12	10	19.0	22	630				
GR14/10S	14	10	20.5	24	630				
GR14/12S	14	12	20.5	24	630			630	
GR16/12S	16	12	20.0	27	400	400			
GR16/14S	16	14	21.5	27	400				
GR20/10S	20	10	22.0	32	400				
GR20/12S	20	12	22.0	32	400			400	
GR20/16S	20	16	23.0	32	400			400	
GR25/16S	25	16	25.5	41	400				
GR25/20S	25	20	25.5	41	400			400	
GR30/20S	30	20	26.0	46	400				
GR30/25S	30	25	26.5	46	400			400	
GR38/30S	38	30	29.5	55	315				

For EO-2 part number, insert "Z" between size and pressure series. Example: GR06/04ZLLCF

Dimensions and pressures for reference only, subject to change.

Visual Index

How To Order

Specs

Assembly / Installation

Reference Section

3-D CAD Model