



GE-R Full Dimensions

Male Connector

24° Flareless / BSPT or BSPP



R (BSPT) thread

Cutting face DIN 3852, form B, G
(BSPP) thread

TUBE FITTING PART #	END SIZE				STANDARD Pressure Rating (bar)		
	1 (mm)	2 BSPT / BSPP	I 1 (mm)	S1 (mm)	EO		
					CF	71	MS
GE04LLR	4	R 1/8 keg.	16.0	11	100		63
GE06LLR	6	R 1/8 keg.	14.5	11	100	100	63
GE08LLR	8	R 1/8 keg.	16.5	12	100	100	63
GE08LLR1/4	8	R 1/4 keg.	20.5	14	100	100	63
GE10LLR	10	R 1/4 keg.	20.5	14	100		63
GE12LLR	12	R 1/4 keg.	20.0	17	100		63
GE12LLR3/8	12	R 3/8 keg.	20.0	17	100		
GE06LR	6	G 1/8 A	8.5	14	315	315	200
GE06LR1/8KEG	6	R 1/8 keg.	15.0	12	315		
GE06LR1/4	6	G 1/4 A	10.0	19	315	315	200
GE06LR3/8	6	G 3/8 A	11.5	22	315		200
GE06LR1/2	6	G 1/2 A	12.0	27	315	315	
GE08LR	8	G 1/4 A	10.0	19	315	315	200
GE08LR1/8	8	G 1/8 A	8.5	14	315	315	
GE08LR1/4KEG	8	R 1/4 keg.	20.0	17	315		
GE08LR3/8	8	G 3/8 A	11.5	22	315	315	200
GE08LR1/2	8	G 1/2 A	12.0	27	315	315	200
GE10LR	10	G 1/4 A	11.0	19	315	315	200
GE10LR1/4KEG	10	R 1/4 keg.	21.0	17	315		
GE10LR3/8	10	G 3/8 A	12.5	22	315	315	
GE10LR1/2	10	G 1/2 A	13.0	27	315	315	200
GE12LR	12	G 3/8 A	12.5	22	315	315	
GE12LR1/4	12	G 1/4 A	12.0	19	315	315	
GE12LR1/4KEG	12	R 1/4 keg.	22.0	19	315		
GE12LR3/8KEG	12	R 3/8 keg.	22.0	19	315		
GE12LR1/2	12	G 1/2 A	13.0	27	315	315	200
GE12LR1/2KEG	12	R 1/2 keg.	24.0	24	315		
GE12LR3/4	12	G 3/4 A	14.0	32	315		
GE15LR	15	G 1/2A	14.0	27	250	250	160
GE15LR3/8	15	G 3/8 A	13.5	24	250	250	160
GE15LR3/8KEG	15	R 3/8 keg.	23.0	24	315		
GE15LR1/2KEG	15	R 1/2 keg.	25.0	24	315		
GE15LR3/4	15	G 3/4 A	15.0	32	250		
GE18LR	18	G 1/2 A	14.5	27	250	250	160
GE18LR3/8	18	G 3/8 A	14.0	27	250		160
GE18LR1/2KEG	18	R 1/2 keg.	25.5	27	315		
GE18LR3/4	18	G 3/4 A	14.5	32	250	250	
GE22LR	22	G 3/4 A	16.5	32	160		100
GE22LR1/2	22	G 1/2 A	16.5	32	160	160	100
GE22LR3/4KEG	22	R 3/4 keg.	29.5	32	160		
GE28LR	28	G 1 A	17.5	41	160	160	100
GE28LR3/4	28	G 3/4 A	17.5	41	160		
GE35LR	35	G 1 1/4 A	17.5	50	160		100
GE35LR1	35	G 1 A	17.5	46	160		
GE42LR	42	G 1 1/2 A	19.0	55	160		100

TUBE FITTING PART #	END SIZE		I 1 (mm)	S1 (mm)	STANDARD Pressure Rating (bar)		
	1 (mm)	2 BSPP			EO		
					CF	71	MS
GE06SR	6	G 1/4 A	13.0	19	400		250
GE06SR1/2	6	G 1/2 A	18.0	27	400		
GE08SR	8	G 1/4 A	15.0	19	400	400	250
GE08SR3/8	8	G 3/8 A	15.5	22	400		
GE10SR	10	G 3/8 A	15.0	22	400	400	250
GE10SR1/4	10	G 1/4 A	14.5	19	400		
GE10SR1/2	10	G 1/2 A	17.5	27	400	400	
GE12SR	12	G 3/8 A	17.0	22	400	400	250
GE12SR1/4	12	G 1/4 A	16.5	22	400	400	
GE12SR1/2	12	G 1/2 A	17.5	27	400	400	
GE14SR	14	G 1/2 A	19.0	27	400		250
GE14SR3/8	14	G 3/8 A	18.5	24	400		
GE16SR	16	G 1/2 A	18.5	27	400	400	250
GE16SR3/8	16	G 3/8 A	18.0	27	400	400	
GE16SR3/4	16	G 3/4 A	20.5	32	400		
GE20SR	20	G 3/4 A	20.5	32	400	400	250
GE20SR1/2	20	G 1/2 A	20.5	32	400	400	
GE25SR	25	G 1 A	23.0	41	250		160
GE25SR3/4	25	G 3/4 A	23.0	41	250		
GE30SR	30	G 1 1/4 A	23.5	50	160		100
GE30SR1	30	G 1 A	23.5	46	160	160	
GE38SR	38	G 1 1/2 A	26.0	55	160		100
GE38SR11/4	38	G 1 1/4 A	26.0	55	160		

Note: "keg." refers to tapered threads.
Not sold with EO-2 Functional Nut.

Dimensions and pressures for reference only, subject to change.

Visual
IndexHow To
Order

Specs

Assembly /
InstallationReference
Section3-D
CAD
Model