


RED Full Dimensions

Tube End Reducer

Flareless Swivel / 24° Flareless

**L-Series**

TUBE FITTING PART #	END SIZE		I 1 (mm)	S1 (mm)	STANDARD Pressure Rating (bar)				
	1 (mm)	2 Metric			EO			EO-2	
					CF	71	MS	CF	71
RED06L/04LL	4	M12 x 1.5	24.5	9	250			250	
RED08/06L	6	M14 x 1.5	23.5	12	250			315	
RED10/06L	6	M16 x 1.5	25	14	315			315	
RED10/08L	8		25	14	315			315	
RED12/06L	6	M18 x 1.5	25	17	315			315	
RED12/08L	8		25	17	315			315	
RED12/10L	10		26	17	315			315	
RED15/06L	6	M22 x 1.5	28.5	19	315			315	
RED15/08L	8		28.5	19	315			315	
RED15/10L	10		29.5	19	315	315		315	
RED15/12L	12		29.5	19	315			315	
RED18/06L	6	M26 x 1.5	28	24	315			315	
RED18/08L	8		28	24	315			315	
RED18/10L	10		29	24	315	315		315	
RED18/12L	12		29	24	315	315		315	
RED18/15L	15		30	24	315			315	
RED22/06L	6	M30 x 2	32	27	160			160	
RED22/08L	8		32	27	160			160	
RED22/10L	10		33	27	160			160	
RED22/12L	12		33	27	160			160	
RED22/15L	15		34	27	160			160	
RED22/18L	18		33.5	27	160	160		160	
RED28/06L	6	M36 x 2	34	32	160			160	
RED28/08L	8		34	32	160			160	
RED28/10L	10		35	32	160			160	
RED28/12L	12		35	32	160			160	
RED28/15L	15		36	32	160			160	
RED28/18L	18		35.5	32	160			160	
RED28/22L	22		37.5	32	160			160	
RED35/12L	12	M45 x 2	38	41				160	
RED35/15L	15		39	41	160			160	
RED35/18L	18		38.5	41	160			160	
RED35/22L	22		40.5	41	160			160	
RED35/28L	28		40.5	41	160			160	
RED42/18L	18	M52 x 2	42	50	160			160	
RED42/22L	22		44	50	160			160	
RED42/28L	28		44	50	160			160	
RED42/35L	35		43	50	160	160		160	

For EO-2 part number, insert "Z" between size and pressure series.
Example: RED08/06ZLCF

S-Series

TUBE FITTING PART #	END SIZE		I 1 (mm)	S1 (mm)	STANDARD Pressure Rating (bar)				
	1 (mm)	2 Metric			EO			EO-2	
					CF	71	MS	CF	71
RED08/06S	6	M16 x 1.5	27.0	14	630			630	
RED10/06S	6	M18 x 1.5	27.5	17	630			630	
RED10/08S	8		27.5	17	630			630	
RED12/06S	6	M20 x 1.5	29.0	17	630			630	
RED12/08S	8		29.0	17	630			630	
RED12/10S	10		29.5	19	630			630	
RED14/06S	6	M22 x 1.5	31.5	19	630				
RED14/08S	8		31.5	19	630				
RED14/10S	10		31.0	19	630				
RED14/12S	12		31.0	22	630			630	
RED16/06S	6	M24 x 1.5	32.0	22	400			400	
RED16/08S	8		32.0	22	400			400	
RED16/10S	10		31.5	22	400			400	
RED16/12S	12		31.5	22	400			400	
RED16/14S	14		33.0	24	400				
RED20/06S	6	M30 x 2	36.0	27	400			400	
RED20/08S	8		36.0	27	400			400	
RED20/10S	10		35.5	27	400			400	
RED20/12S	12		35.5	27	400			400	
RED20/14S	14		37.0	27	400				
RED20/16S	16		36.5	27	400			400	
RED25/06S	6	M36 x 2	38.5	32				400	
RED25/08S	8		38.5	32	400			400	
RED25/10S	10		38.0	32	400			400	
RED25/12S	12		38.0	32	400			400	
RED25/14S	14		39.5	32	400				
RED25/16S	16		39.0	32	400	400		400	
RED25/20S	20		39.0	32	400			400	
RED30/08S	8	M42 x 2	44.0	41				400	
RED30/10S	10		43.5	41	400			400	
RED30/12S	12		43.5	41	400			400	
RED30/14S	14		45.0	41					
RED30/16S	16		44.5	41	400			400	
RED30/20S	20		44.5	41	400			400	
RED30/25S	25		45.0	41	400			400	
RED38/12S	12	M52 x 2	47.0	50	315			315	
RED38/16S	16		48.0	50	315			315	
RED38/20S	20		48.0	50	315			315	
RED38/25S	25		48.5	50	315			315	
RED38/30S	30		49.0	50	315			315	

For EO-2 part number, insert "Z" between size and pressure series.
Example: RED08/06ZSCF

Dimensions and pressures for reference only, subject to change.

Visual
IndexHow To
Order

Specs

Assembly /
InstallationReference
Section3-D
CAD
Model