


TR Full DimensionsTee-Reducer
24° Flareless

TUBE FITTING PART #	END SIZE			I1 (mm)	I2 (mm)	I3 (mm)	S4 (mm)	STANDARD Pressure Rating (bar)				
	1 (mm)	2 (mm)	3 (mm)					EO		EO-2		
								CF	71	MS	CF	71
TR04/08/04LL	4	8	4	13.0	13.0	11.5	12	100				
TR06/04/06LL	6	4	6	9.5	9.5	11.0	11	100				
TR06/08/06L	6	8	6	14.0	14.0	14.0	14	315				
TR08/06/08L	8	6	8	14.0	14.0	14.0	14	315				
TR06/10/06L	6	10	6	15.0	15.0	15.0	14	315				
TR08/10/08L	8	10	8	15.0	15.0	15.0	14	315				
TR10/06/10L	10	6	10	15.0	15.0	15.0	14	315				
TR10/08/10L	10	8	10	15.0	15.0	15.0	14	315				
TR10/10/06L	10	10	6	15.0	15.0	15.0	14	315				
TR08/12/08L	8	12	8	17.0	17.0	17.0	17	315				
TR12/06/12L	12	6	12	17.0	17.0	17.0	17	315				
TR12/08/08L	12	8	8	17.0	17.0	17.0	17	315				
TR12/08/12L	12	8	12	17.0	17.0	17.0	17	315				
TR12/10/10L	12	10	10	17.0	17.0	17.0	17	315				
TR12/10/12L	12	10	12	17.0	17.0	17.0	17	315				
TR12/12/10L	12	12	10	17.0	17.0	17.0	17	315				
TR10/15/10L	10	15	10	21.0	21.0	21.0	19	315				
TR12/15/12L	12	15	12	21.0	21.0	21.0	19	315				
TR15/06/15L	15	6	15	21.0	21.0	21.0	19	315				
TR15/10/15L	15	10	15	21.0	21.0	21.0	19	315				
TR15/12/12L	15	12	12	21.0	21.0	21.0	19	315				
TR15/12/15L	15	12	15	21.0	21.0	21.0	19	315				
TR15/15/12L	15	15	12	21.0	21.0	21.0	19	315				
TR12/18/12L	12	18	12	24.0	24.0	23.5	24	315				
TR18/10/10L	18	10	10	23.5	24.0	24.0	24	315				
TR18/10/18L	18	10	18	23.5	23.5	24.0	24	315				
TR18/12/18L	18	12	18	23.5	23.5	24.0	24	315				
TR18/15/18L	18	15	18	23.5	23.5	24.0	24	315				
TR18/18/10L	18	18	10	23.5	24.0	23.5	24	315				
TR22/10/22L	22	10	22	27.5	27.5	28.0	27	160				
TR22/12/22L	22	12	22	27.5	27.5	28.0	27	160				
TR22/15/15L	22	15	15	27.5	28.0	28.0	27	160				
TR22/15/22L	22	15	22	27.5	27.5	28.0	27	160				
TR22/18/18L	22	18	18	27.5	27.5	27.5	27	160				
TR22/18/22L	22	18	22	27.5	27.5	27.5	27	160				
TR22/22/18L	22	22	18	27.5	27.5	27.5	27	160				
TR28/10/28L	28	10	28	30.5	30.5	31.0	36	160				
TR28/12/28L	28	12	28	30.5	30.5	31.0	36	160				
TR28/15/28L	28	15	28	30.5	30.5	31.0	36	160				
TR28/18/28L	28	18	28	30.5	30.5	30.5	36	160				
TR28/22/22L	28	22	22	30.5	30.5	30.5	36	160				
TR28/22/28L	28	22	28	30.5	30.5	30.5	36	160				

Series S is continued on the next page.

For EO-2 part number, insert "Z" between size and pressure series.
Example: TR06/08/06ZLLCF

Dimensions and pressures for reference only, subject to change.

Visual
IndexHow To
Order

Specs

Assembly /
InstallationReference
Section3-D
CAD
Model