


DVGE-R Full Dimensions

Plain Bearing Rotary Straight
24° Flareless / BSPP with EOlastic Seal*




TUBE FITTING PART #	END SIZE		I 1 (mm)	I 4 (mm)	S 1 (mm)	S 4 (mm)	STANDARD Pressure Rating (bar)		
	1 (mm)	2 BSPP					EO		
							CF	71	MS
DVGE06LR	6	G 1/4 A	21.0	18.0	19	12	40		
DVGE08LR	8	G 1/4 A	21.0	18.0	19	14	40		
DVGE10LR	10	G 3/8 A	25.0	18.0	24	17	40		
DVGE12LR	12	G 1/2 A	27.0	21.0	27	19	40		
DVGE15LR	15	G 3/4 A	32.0	24.0	32	24	40		
DVGE18LR	18	G 1 A	35.0	27.5	41	27	40		
DVGE22LR	22	G 1 A	39.0	27.5	41	32	40		
DVGE28LR	28	G 1 1/4 A	40.5	31.0	50	41	40		
DVGE35LR	35	G 1 1/2 A	44.5	35.0	55	46			
DVGE06SR	6	G 1/4 A	23.0	18.0	19	14			
DVGE08SR	8	G 1/4 A	24.0	18.0	19	17	100		
DVGE10SR	10	G 3/8 A	26.5	18.0	24	19	100		
DVGE12SR	12	G 1/2 A	28.5	21.0	27	22			
DVGE16SR	16	G 3/4 A	33.5	24.0	32	27			
DVGE20SR	20	G 1 A	38.0	27.5	41	32	100		
DVGE25SR	25	G 1 A	40.5	27.5	41	41	100		
DVGE30SR	30	G 1 1/4 A	41.5	31.0	50	46	100		
DVGE38SR	38	G 1 1/2 A	47.0	35.0	55	55			

*Note: Port depth must be deeper than standard DIN 3852-2.

DVWE-R Full Dimensions

Plain Bearing Rotary Elbow
24° Flareless / BSPP with EOlastic Seal*



TUBE FITTING PART #	END SIZE		I 2 (mm)	I 4 (mm)	L 3 (mm)	S 1 (mm)	S 3 (mm)	STANDARD Pressure Rating (bar)		
	1 (mm)	2 BSPP						EO		
								CF	71	MS
DVWE06LR	6	G 1/4 A	12.0	18.0	20.0	19	12	40		
DVWE08LR	8	G 1/4 A	14.0	18.0	21.0	19	12	40		
DVWE10LR	10	G 3/8 A	15.0	18.0	26.0	24	14	40		
DVWE12LR	12	G 1/2 A	17.0	21.0	27.0	27	17	40		
DVWE15LR	15	G 3/4 A	21.0	24.0	33.0	32	19	40		
DVWE18LR	18	G 1 A	23.5	27.5	37.5	41	27	40		
DVWE22LR	22	G 1 A	27.5	27.5	39.5	41	27	40		
DVWE28LR	28	G 1 1/4 A	30.5	31.0	44.0	50	36			
DVWE35LR	35	G 1 1/2 A	34.5	35.0	54.0	55	41			
DVWE06SR	6	G 1/4 A	16.0	18.0	21.0	19	12			
DVWE08SR	8	G 1/4 A	17.0	18.0	22.0	19	14	100		
DVWE10SR	10	G 3/8 A	17.5	18.0	27.0	24	17	100		
DVWE12SR	12	G 1/2 A	21.5	21.0	28.0	27	17	100		
DVWE16SR	16	G 3/4 A	24.5	24.0	34.0	32	24			
DVWE20SR	20	G 1 A	26.5	27.5	39.5	41	27			
DVWE25SR	25	G 1 A	30.0	27.5	42.5	41	36	100		
DVWE30SR	30	G 1 1/4 A	35.5	31.0	48.0	50	41	100		
DVWE38SR	38	G 1 1/2 A	41.0	35.0	55.0	55	50			

*Note: Port depth must be deeper than standard DIN 3852-2.

Dimensions and pressures for reference only, subject to change.

Visual
IndexHow To
Order

Specs

Assembly /
InstallationReference
Section3-D
CAD
Model