


DVGE-M Full Dimensions

Plain Bearing Rotary Straight

24° Flareless / Metric Parallel with EOlastic Seal*

TUBE FITTING PART #	END SIZE		I 1 (mm)	I 4 (mm)	S 1 (mm)	S 3 (mm)	STANDARD Pressure Rating (bar)		
	1	2					EO		
	(mm)	Metric					CF	71	MS
DVGE06LM	6	M 14 x 1.5	20.0	18.0	19	12	40		
DVGE08LM	8	M 14 x 1.5	21.0	18.0	19	12			
DVGE10LM	10	M 18 x 1.5	26.0	18.0	24	14			
DVGE12LM	12	M 22 x 1.5	27.0	21.0	27	17			
DVGE15LM	15	M 27 x 2	33.0	24.0	32	19	40		
DVGE18LM	18	M 33 x 2	37.5	27.5	41	27			
DVGE22LM	22	M 33 x 2	39.5	27.5	41	27			
DVGE28LM	28	M 42 x 2	44.0	31.0	50	36			
DVGE35LM	35	M 48 x 2	54.0	35.0	55	41	100		
DVGE06SM	6	M 14 x 1.5	21.0	18.0	19	12			
DVGE08SM	8	M 14 x 1.5	22.0	18.0	19	14			
DVGE10SM	10	M 18 x 1.5	27.0	18.0	24	17			
DVGE12SM	12	M 22 x 1.5	28.0	21.0	27	17	100		
DVGE16SM	16	M 27 x 2	34.0	24.0	32	24			
DVGE20SM	20	M 33 x 2	39.5	27.5	41	27			
DVGE25SM	25	M 33 x 2	42.5	27.5	41	36			
DVGE30SM	30	M 42 x 2	48.0	31.0	50	41	100		
DVGE38SM	38	M 48 x 2	55.0	35.0	55	50			

*Note: Port depth must be deeper than standard DIN 3852-1.


**DVWE-M** Full Dimensions

Plain Bearing Rotary Elbow

24° Flareless / Metric Parallel with EOlastic Seal*

TUBE FITTING PART #	END SIZE		I 2 (mm)	I 4 (mm)	L 3 (mm)	S 1 (mm)	S 3 (mm)	STANDARD Pressure Rating (bar)		
	1	2						EO		
	(mm)	Metric						CF	71	MS
DVWE06LM	6	M 14 x 1.5	12.0	18.0	20.0	19	12	40		
DVWE08LM	8	M 14 x 1.5	14.0	18.0	21.0	19	12	40		
DVWE10LM	10	M 18 x 1.5	15.0	18.0	26.0	24	14			
DVWE12LM	12	M 22 x 1.5	17.0	21.0	27.0	27	17			
DVWE15LM	15	M 27 x 2	21.0	24.0	33.0	32	19			
DVWE18LM	18	M 33 x 2	23.5	27.5	37.5	41	27			
DVWE22LM	22	M 33 x 2	27.5	27.5	39.5	41	27			
DVWE28LM	28	M 42 x 2	30.5	31.0	44.0	50	36			
DVWE35LM	35	M 48 x 2	34.5	35.0	54.0	55	41			
DVWE06SM	6	M 14 x 1.5	16.0	18.0	21.0	19	12	100		
DVWE08SM	8	M 14 x 1.5	17.0	18.0	22.0	19	14	100		
DVWE10SM	10	M 18 x 1.5	17.5	18.0	27.0	24	17			
DVWE12SM	12	M 22 x 1.5	21.5	21.0	28.0	27	17			
DVWE16SM	16	M 27 x 2	24.5	24.0	34.0	32	24			
DVWE20SM	20	M 33 x 2	26.5	27.5	39.5	41	27			
DVWE25SM	25	M 33 x 2	30.0	27.5	42.5	41	36			
DVWE30SM	30	M 42 x 2	35.5	31.0	48.0	50	41			
DVWE38SM	38	M 48 x 2	41.0	35.0	55.0	55	50			

*Note: Port depth must be deeper than standard DIN 3852-1.



Dimensions and pressures for reference only, subject to change.