




KH Full Dimensions


Two-Way Ball Valve
24° Flareless / 24° Flareless



DN4 - DN25



DN32 - DN40



TUBE FITTING PART #	END SIZE (mm)	DN SIZE (mm)	B (mm)	h1 (mm)	h2 (mm)	H (mm)	L (mm)	L2 (mm)	L3 (mm)	R (mm)	SW1 (mm)	EO			EO-2	
												CF	71	MS	CF	71
KH06L	6	4	20	10.0	55.0	25	67	36	—	76	7	125				
KH08L	8	6	20	10.0	55.0	25	67	36	—	76	7	125				
KH10L	10	8	30	14.5	68.0	35	75	45	—	100	8	125			125	
KH12L	12	10	30	14.5	68.0	35	75	45	—	100	8	125	125		125	
KH15L	15	12	35	17.0	92.0	40	83	51	—	112	10	125	125		125	
KH18L	18	16	45	20.0	105.0	45	82	50	—	166	11	125			125	
KH22L	22	20	45	24.0	113.0	55	99	60	—	187	14				63	
KH28L	28	25	55	26.0	118.0	60	108	70	—	187	14	63			63	
KH35L	35	32	73	36.5	180.5	80	121	79	58.5	240	17					
KH42L	42	40	85	42.5	190.5	90	118	76	52.5	250	17	63				
KH08S	8	4	20	10.0	55.0	25	73	36	—	76	7	200				
KH10S	10	6	20	10.0	55.0	25	73	36	—	76	7	200				
KH12S	12	8	30	14.5	68.0	35	77	45	—	100	8	200				
KH14S	14	10	30	14.5	68.0	35	81	45	—	100	8	200				
KH16S	16	12	35	17.0	92.0	40	87	51	—	112	10	160				
KH20S	20	16	40	20.0	105.0	45	90	50	—	166	11	160	160		160	
KH25S	25	20	45	24.0	113.0	55	107	60	—	187	14	125				
KH30S	30	25	55	36.0	118.0	60	120	70	—	187	14	125				
KH38S	38	32	73	36.5	180.5	80	127	73	58.5	320	17	63				

For EO-2 part number, insert "Z" between size and pressure series.
Example: KH08ZSCF. Omit "CF" in the part number for steel material.

Dimensions and pressures for reference only, subject to change.