




Port Ends for SAE J1926-1 (ISO 11926-1) Port



**SAE J1926
Adjustable**



**SAE J1926
Nonadjustable**



**SAE J1926-1
Port²⁾**

	Thread	Locknut Hex	Drill	Minimum Thread	Stud Length	
SIZE	T UN/UNF	C4 (inch)	D Max (inch)	L4 Min (inch)	X (inch)	Z Max (inch)
LIGHT DUTY (TRIPLE-LOK, FERULOK, ADAPTERS)						
2	5/16-24	7/16	0.063	0.390	0.297	0.36
3	3/8-24	1/2	0.125	0.390	0.297	0.33
4	7/16-20	9/16	0.172	0.454	0.360	0.39
5	1/2-20	5/8	0.234	0.454	0.360	0.43
6	9/16-18	11/16	0.297	0.500	0.391	0.43
8	3/4-16	7/8	0.391	0.562	0.438	0.49
10	7/8-14	1	0.484	0.656	0.500	0.56
12	1 1/16-12	1 1/4	0.609	0.750	0.594	0.65
14	1 3/16-12	1 3/8	0.719	0.750	0.594	0.65
16	1 5/16-12	1 1/2	0.844	0.750	0.594	0.65
20	1 5/8-12	1 7/8	1.078	0.750	0.594	0.65
24	1 7/8-12	2 1/8	1.312	0.750	0.594	0.65
32	2 1/2-12	2 3/4	1.781	0.750	0.594	0.59
HEAVY DUTY (SEAL-LOK)						
2	5/16-24	1/2	0.063	0.390	0.374	0.38
3	3/8-24	9/16	0.125	0.390	0.374	0.39
4	7/16-20	5/8	0.172	0.454	0.433	0.43
5	1/2-20	11/16	0.236	0.454	0.433	0.44
6	9/16-18	3/4	0.264	0.500	0.472	0.47
8	3/4-16	15/16	0.378	0.562	0.551	0.54
10	7/8-14	1 1/16	0.484	0.656	0.630	0.63
12	1 1/16-12	1 3/8	0.609	0.750	0.728	0.73
14	1 3/16-12	1 1/2	0.709	0.750	0.728	0.73
16	1 5/16-12	1 5/8	0.811	0.750	0.728	0.73
20	1 5/8-12	1 7/8	1.024	0.750	0.728	0.73
24	1 7/8-12	2 1/8	1.260	0.750	0.728	0.73
32	2 1/2-12	2 3/4	1.575	0.750	0.728	0.73

1) See [page O3](#) for SAE O-rings.

2) See [page U26](#) for port details.

Dimensions and pressures for reference only, subject to change.