


F4OHG5 Full Dimensions


Conversion Adapter
BSPP-ORR / SAE-ORB
(for ISO 1179-1 / DIN 3852-2 Port)



TUBE FITTING PART #	END SIZE		C1 HEX (in.)	L (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1	2			-S	-SS	-B
	BSPP	UN/UNF-2B					
1/8-4F4OHG5	1/8-28	7/16-20	11/16	1	5.0		
1/4-4F4OHG5	1/4-19	7/16-20	3/4	1.11	5.0		
1/4-6F4OHG5	1/4-19	9/16-18	13/16	1.25	5.0		
3/8-4F4OHG5	3/8-19	7/16-20	7/8	1.19	5.0		
3/8-5F4OHG5	3/8-19	1/2-20	7/8	1.19	5.0		
3/8-6F4OHG5	3/8-19	9/16-18	7/8	1.25	5.0	5.0	
3/8-8F4OHG5	3/8-19	3/4-16	1	1.33	5.0		
1/2-10F4OHG5	1/2-14	7/8-14	1 1/8	1.6	3.5		
3/4-12F4OHG5	3/4-14	1 1/16-12	1 3/8	1.74	3.5	3.5	
1-16F4OHG5	1-11	1 5/16-12	1 3/4	1.92	3.5		
1 1/4-16F4OHG5	1 1/4-11	1 5/16-12	2	1.95	2.0		
1 1/4-20F4OHG5	1 1/4-11	1 5/8-12	2	1.95	2.0		

F4OHG Full Dimensions


Conversion Adapter
BSPP-ORR / NPTF
(for ISO 1179-1 / DIN 3852-2 Port)



TUBE FITTING PART #	END SIZE		C6 HEX (in.)	L (in)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1	2			-S	-SS	-B
	BSPP	NPTF					
1/8x1/8F4OHG	1/8-28	1/8-27	5/8	0.97	5		
1/4x1/4F4OHG	1/4-19	1/4-18	3/4	1.28	5		
3/8x3/8F4OHG	3/8-19	3/8-18	7/8	1.33	5		
1/2x1/2F4OHG	1/2-14	1/2-14	1 1/8	1.73	3.5		
3/4x3/4F4OHG	3/4-14	3/4-14	1 3/8	1.77	3.5		
1x1F4OHG	1-11	1-11 1/2	1 5/8	2.17	3		

PTR34 Full Dimensions

BSPT Reducing Adapter
BSPT / BSPP



TUBE FITTING PART #	END SIZE		C HEX (in.)	L2 (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)		
	1	2			-S	-SS	-B
	BSPT	BSPP					
1/4X1/8PTR34M	1/4-19	1/8-28	17	28	6.0		
3/8X1/4PTR34M	3/8-19	1/4-19	19	33	6.0		
1/2X1/4PTR34M	1/2-14	1/4-19	22	39	5.0		
1/2X3/8PTR34M	1/2-14	3/8-19	22	39	5.0		

Dimensions and pressures for reference only, subject to change.

Visual
Index

Specs

Assembly /
Installation3-D
CAD
ModelReference
Section