


EO Diagnostic Swivels


EO Diagnostic Swivels are commonly used on EO tees (24° flareless - DIN 2353) where periodic pressure and temperature checks are required. The M16 x 2 diagnostic tip mates with the SMA3 diagnostic nose offered by Parker's Quick Coupling Division.

VKA3

M16 x 2.0 Diagnostic
Tip / EO Swivel



Type A



Type B

TUBE FITTING PART # STEEL	TYPE	D1 TUBE O.D. (mm)	G Metric	H REF. (mm)	SW1 (mm)	SW2 (mm)	STANDARD Pressure (x 1,000 PSI)	
							Static	Dynamic
							A3C	A3C
VKA3/06LA3C	A	6	M12 x 1.5	55	17	17	7.2	4.5
VKA3/08LA3C	A	8	M14 x 1.5	51	17	17	7.2	4.5
VKA3/10LA3C	A	10	M16 x 1.5	53	17	19	7.2	4.5
VKA3/12LA3C	A	12	M18 x 1.5	53	17	22	5.8	4.5
VKA3/15LA3C	B	15	M22 x 1.5	59	17	27	5.8	4.5
VKA3/18LA3C	B	18	M26 x 1.5	59	17	32	5.8	4.5
VKA3/22LA3C	B	22	M30 x 2	60	17	39	3.6	2.3
VKA3/28LA3C	B	28	M36 x 2	64	17	41	3.6	2.3
VKA3/35LA3C	B	35	M45 x 2	71	17	50	3.6	2.3
VKA3/42LA3C	B	42	M52 x 2	72	17	60	3.6	2.3
VKA3/06SA3C	A	6	M14 x 1.5	50	17	17	10.1	9.1
VKA3/08SA3C	A	8	M16 x 1.5	52	17	19	10.1	9.1
VKA3/10SA3C	A	10	M18 x 1.5	53	17	22	10.1	9.1
VKA3/12SA3C	A	12	M20 x 1.5	54	19	24	10.1	9.1
VKA3/14SA3C	B	14	M22 x 1.5	59	17	27	10.1	9.1
VKA3/16SA3C	B	16	M24 x 1.5	58	17	30	9.1	5.8
VKA3/20SA3C	B	20	M30 x 2	65	17	36	9.1	5.8
VKA3/25SA3C	B	25	M36 x 2	68	17	46	9.1	5.8
VKA3/30SA3C	B	30	M42 x 2	74	17	50	6.0	5.8
VKA3/38SA3C	B	38	M52 x 2	81	17	60	6.0	4.5

Dimensions and pressures for reference only, subject to change.