


Pressure Gauge Sealing Ring



Specify size and material


Examples: DK11/2CFX (steel)
DK11/271X (stainless steel)

TUBE FITTING PART #	FOR INTERNAL THREAD	D (mm)	D1 (mm)	H (mm)	STANDARD From Stock		
					CFX	71	MS
DK11/4	G 1/4	6	11.3	4.5	•	•	
DK11/2	G 1/2	12	18.5	5.0	•	•	

EO O-Ring

Specify size and compound

Examples: OR4.5X1.5X (standard NBR)
OR4.5X1.5VITX (optional FPM)



Application range see following identification numbers 1 to 4

Application:

- 1=Weld nipples, swivel nuts e.g. SKA, EW, EV, EL, ET, VKA, RED
- 2=WH/TH
- 3=DVGE/DVWE
- 4=Hydr. flanges BFG/BFW

TUBE FITTING PART #	D (mm)	H (mm)	#	APPLICATION Size	STANDARD From Stock	
					NBR*	FPM**
OR4.5X1.5X	4.5	1.5	1	6L, 6S	•	•
OR6.5X1.5X	6.5	1.5	1	8L, 8S	•	•
OR8X1.5X	8.0	1.5	1	10L, 10S	•	•
OR9.3X1.5X	9.3	1.5	2	G 1/8, M12, M14	•	•
OR10X1.5X	10.0	1.5	1	12L, 12S	•	•
OR11X2X	11.0	2.0	1	14S	•	•
OR12.5X1.5X	12.5	1.5	2	G 1/4, M12, M14	•	•
OR13X2X	13.0	2.0	1	16S	•	•
OR15X2X	15.0	2.0	1	18L	•	•
OR16X1.5X	16.0	1.5	2	G 3/8, M16	•	•
OR16.3X2.4X	16.3	2.4	1	20S	•	•
OR17X3X	17.0	3.0	3		•	
OR18X1.5X	18.0	1.5	2	M18	•	•
OR20X1.5X	20.0	1.5	2	G 1/2, M20	•	•
OR20X2X	20.0	2.0	1	22L	•	•
OR20X2.5X	20.0	2.5	4	LK 35	•	•
OR20.3X2.4X	20.3	2.4	1	25S	•	•
OR23.4X3.56X	23.4	3.6	3		•	
OR25X2X	25.0	2.0	2	G 3/4, M26, M27	•	•
OR25.3X2.4X	25.3	2.4	1	30S	•	•
OR26X2X	26.0	2.0	1	28L	•	•
OR26X2.5X	26.0	2.5	4	LK40	•	•
OR31X4X	31.0	4.0	3		•	
OR32X2.5X	32.0	2.5	1	35L	•	•
OR33X2.5X	33.0	2.5	2, 4	G1, M33, LK55	•	•
OR33.3X2.4X	33.3	2.4	1	38S	•	•
OR34.5X3.53X	34.5	3.5	3		•	
OR38X2.5X	38.0	2.5	1	42L	•	•
OR41X2.5X	41.0	2.5	2	G 1 1/4, M42	•	•
OR46X3X	46.0	3.0	2	G 1 1/2, M48	•	•

* NBR is standard compound — 90-durometer Nitrile.

** FPM is optional 90-durometer fluorocarbon compound.

For relating the O-ring sizes to the different fittings, see the [EO/EO-2 Section](#) (Section F).

Dimensions for reference only, subject to change.