



Super-Lube® PTFE Grease

Super-Lube® is developed for lubricating against friction and wear of mating components. It withstands temperatures ranging from -45°F to +450°F.

Part Description	Part No.
Super-Lube® 11 oz. Aerosol	20029



Fig. S127 — Super-Lube

Loctite Penetrating Oil

This product penetrates, lubricates and displaces moisture in mating components. Loctite Penetrating Oil also protects against rust and corrosion.

Part Description	Part No.
16 oz. Aerosol.....	51221



Fig. S128 — Loctite Penetrating Oil

O-Ring Lubricants

Parker O-Lube

O-Lube is an outstanding general-purpose grease intended for use with O-rings and other seals in hydraulic and pneumatic systems. The temperature range is from -29°C to +82°C (-20°F to +180°F).

Part Description	Part No.
O-ring Lubricant.....	OLUBE-884-4-TFD



Fig. S129 — Parker O-Lube

Parker Super O-Lube

Super O-Lube is an all-purpose O-ring lubricant. It is not a grease, but rather a high-viscosity silicone oil. The temperature range is -54°C to +204°C (-65°F to +400°F).

Part Description	Part No.
O-ring Lubricant.....	SLUBE-884-2-TFD



Fig. S130 — Parker Super O-Lube

Dimensions and pressures for reference only, subject to change.