Featuring...Snap-tite quality with superior pressure and flow characteristics over the competition.



- Flush Face/Dry Break design facilitates easy cleaning prior to connection
- High strength steel construction
- Heavy duty zinc yellow dichromate plating for exceptional corrosion resistance
- Sizes 1/4", 3/8", 1/2", 5/8", 3/4" & 1" (6.3, 10, 12.5, 16, 19 & 25 mm)
- Push-to-connect design
- Industry Interchangeability couplers and nipples are interchangeable with other manufacturer's ISO 16028 couplings
- Connect Under Pressure Capability currently available in 1/2" size in either coupler or nipple half
- 4:1 Safety factor
- 3/8" size also conforms to HTMA (Hydraulic Tool Manufacturers Association) standards

Snap-tite's expanded 74 Series product line is designed to meet or exceed the requirements called out in ISO 16028. The 3/8" unit also meets or exceeds the requirements as established by HTMA specifications and defined by ANSI/NFPA T3.20.15-1991.

In addition, Snap-tite's patented Series CP74 coupling is designed to meet a multitude of issues presently faced by users worldwide. Trapped pressure, whether residual or created by thermal expansion, prevents standard quick connect couplings from connecting as designed. Construction, portable hydraulic tools and utility equipment are a few of the many industries where connections made under pressure would save valuable time and money. Snap-tite's Series CP74 is "The Answer" to this dilemma.

The connect under pressure (CP) option allows either coupling half to be placed on the pressurized portion of the hydraulic circuit with static pressure up to 3625 psi (250 bar). It can then easily connect to Snap-tite's 74 Series or any other ISO 16028 mate of the same size without damage to the coupling or endangering the environment with subsequent spillage. Durability, reliability and concern for the environment were considered when designing Snap-tite's 74 Series coupling featuring one hand, push-to-connect and disconnect convenience.

