

# ORDERING INFORMATION

## Fixed Inline Flow Control Valves

**FRI 05 - 2 P - 2.5 A**

Series	Max. Flow Rating	Port Size		Port Thread Type	Required Flow <i>(info on pg. 2)</i>	Seal
		<i>NPTF or RP</i>	<i>SAE</i>		<i>GPM</i>	
Fixed Flow	<b>05</b> - 5 gpm (20 l/min.)	<b>2</b> - 1/4	<b>4</b> - 1/4	<b>P</b> - NPTF		No-Letter-
Regulator	<b>10</b> - 10 gpm (40 l/min.)	<b>3</b> - 3/8	<b>6</b> - 3/8	<b>S</b> - SAE		Viton (std.)
Inline	<b>15</b> - 15 gpm (55 l/min.)	<b>4</b> - 1/2	<b>8</b> - 1/2	<b>RP</b> - Female British Parallel BS2779		<b>A</b> - Buna
	<b>30</b> - 30 gpm (115 l/min.)	<b>6</b> - 3/4	<b>12</b> - 3/4			
		<b>8</b> - 1	<b>16</b> - 1			

## Adjustable Inline Flow Control Valves

**FRIA 05 - 2 P A**

Series	Max. Flow Rating	Port Size		Port Thread Type	Seal
		<i>NPTF or RP</i>	<i>SAE</i>		
Flow	<b>05</b> - 5 gpm (20 l/min.)	<b>2</b> - 1/4	<b>4</b> - 1/4	<b>P</b> - NPTF	No-Letter-
Regulator	<b>10</b> - 10 gpm (40 l/min.)	<b>3</b> - 3/8	<b>6</b> - 3/8	<b>S</b> - SAE	Viton (std.)
Inline	<b>15</b> - 15 gpm (55 l/min.)	<b>4</b> - 1/2	<b>8</b> - 1/2	<b>RP</b> - Female British Parallel BS2779	<b>A</b> - Buna
Adjustable	<b>30</b> - 30 gpm (115 l/min.)	<b>6</b> - 3/4	<b>12</b> - 3/4		
		<b>8</b> - 1	<b>16</b> - 1		

### ! WARNING !

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

This document and other information from Snap-tite, Inc., its subsidiaries and authorized distributors provide product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operation conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance, safety and warning requirements of the application are met.

The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Snap-tite, Inc. and its subsidiaries at any time without notice.

Distributed by:

