



## 71 Series - Drybreak, Flush Face Couplings

<b>Style</b>	Double Shut-off
<b>ISO Interchange</b>	None
<b>Max. Working Pressure</b>	10,000 psi (690 bar)
<b>Sizes Available</b>	1/8" through 2" nominal diameter
<b>Material</b>	316 Stainless Steel or <sup>(1)</sup> Exotic Alloy
<b>Features</b>	<ul style="list-style-type: none"><li>• Flat-face design simplifies contaminant inspection and cleaning</li><li>• Flush Valve virtually eliminates fluid loss and air inclusion</li><li>• Wide Variety of specialty seal options available</li><li>• Sleeve-Lock option prevents accidental disconnection</li></ul>




## 25 Series - Poppet Style, Chemical Couplings

<b>Style</b>	Double Shut-off or Straight-Through combination
<b>ISO Interchange</b>	None
<b>Max. Working Pressure</b>	1,000 psi (69 bar)
<b>Sizes Available</b>	1/4" through 1/2" nominal diameter
<b>Material</b>	316 Stainless Steel or <sup>(1)</sup> Exotic Alloy
<b>Features</b>	<ul style="list-style-type: none"><li>• Designed for difficult or aggressive media</li><li>• Teflon Seals are standard</li><li>• Tubular barrel valve design enhances flow rate</li><li>• Sleeve-Lock option prevents accidental disconnection</li></ul>



## K Series - Poppet Style, Cryogenic Couplings

<b>Style</b>	Double Shut-off or Straight-Through combination
<b>ISO Interchange</b>	None
<b>Max. Working Pressure</b>	1,000 psi (69 bar)
<b>Sizes Available</b>	3/8" through 2" nominal diameter
<b>Material</b>	316 Stainless Steel or <sup>(1)</sup> Exotic Alloy
<b>Features</b>	<ul style="list-style-type: none"><li>• Cryogenic operation to -400°F/-240°C</li><li>• Designed for difficult or aggressive media</li><li>• Teflon or Kel F Seals are standard options</li><li>• Sleeve-Lock option prevents accidental disconnection</li></ul>



## 28-1 Series - Drybreak, Low Pressure-Low Profile Couplings

<b>Style</b>	Double Shut-off
<b>ISO Interchange</b>	None
<b>Max. Working Pressure</b>	1,000 psi (69 bar)
<b>Sizes Available</b>	1/4" through 2" nominal diameter
<b>Material</b>	316 Stainless Steel, Aluminum
<b>Features</b>	<ul style="list-style-type: none"><li>• Recessed coupling face eases hidden connections</li><li>• Lightweight, Low-profile design</li><li>• Flush Valve virtually eliminates fluid loss and air inclusion</li><li>• Wide variety of specialty seal options available</li><li>• Color coded positive connection indicator</li></ul>

(1) - Specially wetted metal parts such as Inconel, Hastelloy™, and others can be made available. Please consult factory.