

# **HY-FLEX™200/275/300 DOCK**-**NYLON/UHMWPE TUBE** (Rough Bore)

Hi-Flex Dock hose is ideal for use with chemicals, oils and hydrocarbons to 100%, as well as MTBE's to 100%. This hose comes in three grades of working pressures, 200, 275 and 300 for higher pressure applications. These working pressures are due to the polyester tire cord with steel wire helix(es) reinforcement. The nylon tube liner allows a smooth flow of product through the system. All Thermoid dock loading hose meets U.S. Coast Guard requirements.



## Resistance:



#### **Branding:**

Thermoid/HBD Industries Hy-Flex OS&D 275 psi WP Conforms to USCG 33 CFR 1545 suitable for up to 100% aromatics Made In USA



#### Resistance:



### **Branding:**

Thermoid/HBD Industries Hy-Flex OS&D 300 psi WP Conforms to USCG 33 CFR 1545 suitable for up to 100% aromatics Made In USA

**Cover Color:** Black Oil Resistance: High Construction:

> Tube: Round, galvanized bore wire, plain unbonded

nylon liner, UHMWPE liner

Cover:

Reinforcement: Polyester tire cord, high strength

steel wire helix(es)

-20°F to +180°F Temperature Range:

-29°C to +82°C

Packaging: Hand built

Couplings: Swage. Fixed or floating 150# or 300#

flange each end

#### HY-FLEX 200

Product Number	Nominal I.D. (inches) (mm)		Nominal O.D. (inches) (mm)		Plies	Working (psi)	Pressure (Mpa)	Min. Ben (inches)	d Radius (mm)	(lb/ft)	e <b>ight</b> (Kg/m)
34854210502▲	4	101.60	5.19	131.76	2	200	1.38	14.00	355.60	4.50	6.70
34854215502▲	6	152.40	7.50	190.50	2	200	1.38	21.00	533.40	8.40	12.50
34854220502▲	8	203.20	9.75	247.65	4	200	1.38	29.00	736.60	14.00	20.84
34854225502▲	10	254.00	11.94	303.21	6	200	1.38	36.00	914.40	22.50	33.49

All sizes have 30 inches of mercury vaccuum

# **HY-FLEX 275**

Product Number	Nominal I.D. (inches) (mm)		Nominal O.D. (inches) (mm)		Plies	Working (psi)	Pressure (Mpa)	Min. Ben (inches)	d Radius (mm)	(lb/ft)	e <b>ight</b> (Kg/m)
34854240502▲	4	101.60	5.25	133.35	4	275	1.90	16.00	406.40	4.50	6.70
34854245502▲	6	152.40	7.50	190.50	4	275	1.90	21.00	533.40	8.40	12.50
34854250502▲	8	203.20	9.94	252.41	4	275	1.90	31.00	787.40	16.00	23.81
34854255502▲	10	254.00	11.94	303.21	6	275	1.90	38.00	965.20	22.50	33.49

All sizes have 30 inches of mercury vaccuum

#### HY-FLEX 300

Product Number	Nominal I.D. (inches) (mm)		Nominal O.D. (inches) (mm)		Plies	Working Pressure (psi) (Mpa)		Min. Bend Radius (inches) (mm)		Weight (Ib/ft) (Kg/m)	
34854270502▲	4	101.60	5.25	133.35	4	300	2.07	16.00	406.40	4.50	6.70
34854275502▲	6	152.40	7.50	190.50	4	300	2.07	23.00	584.20	8.40	12.50
34854280502▲	8	203.20	9.94	252.41	6	300	2.07	31.00	787.40	15.00	22.32
34854285502▲	10	254.00	11.94	303.21	6	300	2.07	38.00	965.20	22.50	33.49

All sizes have 30 inches of mercury vaccuum

▲ = Make To Order (MTO)