WATER/FIRE water

Hose information is subject to change. For full details, visit our website or contact Customer Service.

## **WASHING MACHINE DRAIN**

This hose is specifically designed to withstand the heat and service life requirements needed for washing machine applications both in domestic and commercial use. It features an EPDM tube and cover with multi-spiral polyester construction. This unique spiral reinforcement helps make this hose kink resistant and easy to handle. This hose is very flexible and ideal for curves and bends.



Cover Color:	Black
Oil Resistance:	Limited
Construction:	
Tube:	EPDM
Cover:	EPDM
Reinforcement:	Spiral polyester yarn
Temperature Range:	-40°F to +200°F -40°C to +93°C
Packaging:	50 ft. lengths – 1 per carton

Product	<b>Nominal I.D.</b>		Nominal O.D.		Reinforcement SpiralsWorking Pressure (psi)		Min. Bend Radius		Weight		
Number	(inches) (mm)		(inches) (mm)				(inches) (mm)		(Ib/ft) (Kg/m)		
00548610250▲	5/8	15.88	0.91	23.02	2 2	62	0.43	3.75	95.25	0.19	0.28
00548614250	7/8	22.23	1.22	30.96		37	0.25	5.25	133.35	0.35	0.52

▲ = Make To Order (MTO)

## WASHING MACHINE INLET

This hose is specifically designed for the long service life and varying water temperature requirements needed in washing machine fill hose applications. It features an EPDM tube and cover. These features combined with high strength characteristics of the reinforcing polyester yarn provide excellent wear and service life. This unique spiral reinforcement helps make this hose resist kinks and is easy to handle. It is very flexible and ideal for curves or bends.

		Resistance:	
	-	00	
		Branding:	
		None	
Cover Color:	Black		

Black
Limited
EPDM
EPDM
Spiral polyester yarn
-40°F to +200°F
-40°C to +93°C
Reels

Product	Nominal I.D.		<b>Nominal O.D.</b>		Reinforcement	Working Pressure		Min. Bend Radius		<b>Weight</b>	
Number	(inches) (mm)		(inches) (mm)		Spirals	(psi) (Mpa)		(inches) (mm)		(lb/ft) (Kg/m)	
00548106100▲	3/8	9.53	0.66	16.67	2	200	1.38	2.25	57.15	0.13	

▲ = Make To Order (MTO)

