

SS269 SOFTWALL MARINE EXHAUST HOSE

- Heavy duty softwall marine exhaust hose for use as a flexible connection to transfer wet exhaust on marine engines.
- Heat resistant tube handles high temperatures found in marine engine compartments.
- Durable heat, ozone, and abrasion resistant cover.

Meets U.S.C.G TYPE Standards for specification SAE J2006 R1.

Tube: Extruded specially compounded Nitrile.
Reinforcement: Textile.
Cover: Specially compounded Nitrile.
Temperature: -40° to +200°F.



I.D.	O.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
1"	1 ⁷ / ₁₆ "	2 plies	200	.46
1 ¹ / ₈ "	1 ⁹ / ₁₆ "	2 plies	200	.49
1 ¹ / ₄ "	1 ¹³ / ₁₆ "	2 plies	200	.69
1 ⁵ / ₁₆ "	1 ⁷ / ₈ "	2 plies	200	.71
1 ³ / ₈ "	1 ¹⁵ / ₁₆ "	2 plies	200	.75
1 ¹ / ₂ "	2 ¹ / ₁₆ "	2 plies	200	.82
1 ⁵ / ₈ "	2 ³ / ₁₆ "	2 plies	200	.87
1 ³ / ₄ "	2 ⁵ / ₁₆ "	2 plies	200	.92
1 ⁷ / ₈ "	2 ⁷ / ₁₆ "	2 plies	200	.97
2"	2 ⁹ / ₁₆ "	2 plies	200	1.07
2 ¹ / ₈ "	2 ¹¹ / ₁₆ "	2 plies	200	1.12
2 ¹ / ₄ "	2 ¹³ / ₁₆ "	2 plies	200	1.17
2 ³ / ₈ "	2 ¹⁵ / ₁₆ "	2 plies	200	1.25
2 ¹ / ₂ "	3 ¹ / ₁₆ "	2 plies	200	1.32
2 ⁵ / ₈ "	3 ³ / ₁₆ "	2 plies	200	1.37
2 ³ / ₄ "	3 ⁵ / ₁₆ "	2 plies	200	1.42
2 ⁷ / ₈ "	3 ⁷ / ₁₆ "	2 plies	200	1.52
3"	3 ⁵ / ₈ "	4 plies	200	1.46
3 ¹ / ₂ "	4 ¹ / ₈ "	4 plies	200	1.70
4"	4 ⁵ / ₈ "	4 plies	200	1.93
4 ¹ / ₂ "	5 ¹ / ₈ "	4 plies	200	2.21
5"	5 ¹⁵ / ₁₆ "	6 plies	200	3.80
5 ⁹ / ₁₆ "	6 ¹ / ₂ "	6 plies	200	4.14
6"	6 ¹⁵ / ₁₆ "	6 plies	200	4.51
6 ⁵ / ₈ "	7 ⁹ / ₁₆ "	6 plies	200	5.01
7"	7 ¹⁵ / ₁₆ "	6 plies	200	5.24
8"	8 ¹⁵ / ₁₆ "	6 plies	150	5.83
8 ⁵ / ₈ "	9 ¹ / ₂ "	6 plies	150	5.95
10"	10 ³ / ₄ "	6 plies	150	6.77
10 ³ / ₄ "	11 ⁵ / ₈ "	6 plies	100	7.55
12"	12 ⁷ / ₈ "	6 plies	100	8.38
12 ³ / ₄ "	13 ⁵ / ₈ "	6 plies	100	8.88