EWC777 CORRUGATED MATERIAL HANDLING HOSE - 5/16" NATURAL RUBBER TUBE

 Corrugated vacuum hose for transferring highly abrasive slurries.

Designed for on the job engineering of specified lengths.
 Hose can be cut, coupled, and installed in minutes at the job site with our split-lok flange coupling system.

Tube: 56" Natural Rubber.

Reinforcement: High strength tire cord with steel wire helix.

Cover: Corrugated SBR. **Temperature:** -40° to +150°F.

I.D.	0.D.	BEND RADIUS	WORKING Pressure Psi	WEIGHT LB/FT	VACUUM
4"	5 ¹ / ₂ "	19"	150	5.00	Full
5"	6 ¹ /2"	24"	150	7.00	Full
6"	71/2"	29"	150	9.00	Full
8"	91/2"	38"	150	12.10	Full
10"	11 ¹ / ₂ "	48"	150	16.00	Full
12"	133/4"	58"	150	23.00	Full
14"	15³/4"	68"	150	27.00	Full
16"	173/4"	78"	125	31.10	Full
18"	20"	88"	125	42.00	Full
20"	22"	100"	100	48.00	Full
22"	24 ⁵ /16"	120"	100	65.00	Full
24"	26 ⁵ /16"	130"	100	69.00	Full

Custom Made Hose Product

Split-Lok Flange Couplings recommended for on-site recoupling.





Split-Lok Flange Couplings (page 70)

EWC789 CORRUGATED VACUUM TRUCK HOSE - 1/2" SBR TUBE

 Corrugated vacuum hose designed for debris suction and mobile vacuum trucks in cleaning storm drains and sewers.

• Dual wire helix provides excellent vacuum capabilities.

Tube: ½" SBR.

Reinforcement: High strength textile with dual wire helix.

Cover: Corrugated SBR.
Temperature: -40° to +150°F.

I.D.	0.D.	BEND RADIUS	WORKING Pressure PSI	WEIGHT LB/FT	VACUUM
4"	5 ¹³ /64"	18"	150	5.00	Full
6"	713/64"	28"	150	7.20	Full
8"	9 ⁵ / ₁₆ "	36"	100	9.50	Full
10"	11 ¹³ /32"	42"	100	11.50	Full

Custom Made Hose Product

Larger size I.D.'s available upon request.

